



Geotechnical Investigation for Pre-Construction Support of Future Development

**Active Petro-Canada Retail Fuel Outlet No. 65044
6250 Hazeldean Rd, Ottawa, Ontario**

Suncor Energy Products Partnership

3275 Rebecca Street, Oakville, ON L6L 6N5

Prepared by:

SLR Consulting (Canada) Ltd.

871 Equestrian Court, Unit 1, Oakville, ON L6L 6L7

SLR Project No.: 216.030133.00001

March 11, 2026

Revision: 0

Revision Record

Revision	Date	Prepared By	Checked By	Authorized By
0	March 11, 2026	I. Budwal	M.D. St. Denis	M.D. St. Denis



Notice – Access to Information Act

These documents and the information contained in them are confidential property of Suncor Energy Products Partnership, and any disclosure of same is governed by the provisions of each of the applicable provincial or territorial Freedom of Information legislation, the Privacy Act (Canada) 1998-81-82-83, c.111, Sch. II "1", and the Access to Information Act (Canada) 1980-81-82-83, c.111, Sch. I "1", as such legislation may be amended or replaced from time to time.



Statement of Limitations

This report has been prepared by SLR Consulting (Canada) Ltd. (SLR) for Suncor Energy Products Partnership (Client) in accordance with the scope of work and all other terms and conditions of the agreement between such parties. SLR acknowledges and agrees that the Client may provide this report to government agencies, interest holders, and/or Indigenous communities as part of project planning or regulatory approval processes. Copying or distribution of this report, in whole or in part, for any other purpose other than as aforementioned is not permitted without the prior written consent of SLR.

Any findings, conclusions, recommendations, or designs provided in this report are based on conditions and criteria that existed at the time work was completed and the assumptions and qualifications set forth herein. SLR may have used AI in the preparation of this document.

This report may contain data or information provided by third party sources on which SLR is entitled to rely without verification and SLR does not warranty the accuracy of any such data or information.

Nothing in this report constitutes a legal opinion nor does SLR make any representation as to compliance with any laws, rules, regulations, or policies established by federal, provincial, territorial, or local government bodies, other than as specifically set forth in this report. Revisions to legislative or regulatory standards referred to in this report may be expected over time and, as a result, modifications to the findings, conclusions, or recommendations may be necessary.



Table of Contents

Statement of Limitations	ii
Acronyms and Abbreviations	v
1.0 Introduction	1
2.0 Project Understanding	1
3.0 Scope of Work	1
4.0 Field Investigation	1
4.1 Drilling Investigation	1
4.2 Laboratory Testing	3
5.0 Subsurface Conditions	3
5.1 Site and Regional Geology	3
5.2 Soil Conditions	3
5.2.1 Topsoil	4
5.2.2 Pavement Structure	4
5.2.3 Fill Materials	4
5.2.4 Sand	4
5.3 Groundwater	5
6.0 Geotechnical Investigation and Recommendations	5
6.1 Geotechnical Parameters	6
6.2 Shallow Foundations for Kiosk Expansion	8
6.3 Floor Slab	9
6.4 Earthbins	9
6.4.1 Support and Bedding	9
6.4.2 Bearing Resistance	10
6.5 Frost Protection Recommendations	10
6.6 Lateral Earth Pressure	10
6.7 Excavation and Backfilling	10
6.8 Seismic Site Classification	11
6.9 Proof Rolling	12
6.11 Geotechnical Quality of Excavated Soils	14
6.12 Preconstruction Condition Survey	14
6.13 Field Review and Quality Control	15
7.0 Closure	15
8.0 References	16



Tables in Text

Table 1: Summary of Boreholes	2
Table 2: Summary of Particle Size Analysis Testing	3
Table 3: Summary of Corrosivity (Sulfate, Chloride, pH and Resistivity) Testing	3
Table 4: Existing Pavement Structure.....	4
Table 5: Summary of Groundwater Level Readings	5
Table 6: Estimated Geotechnical Soil Parameters.....	7
Table 7: Bearing Values for Kiosk Expansion	8
Table 8: AASHTO 1993 Pavement Design Parameters.....	12
Table 9: Pavement Structure	13

Appended Figures

Figure 1: Site Location
Figure 2: Site Plan and Sampling Locations
Figure 3: Proposed Site Layout
Figure 4: Guidelines for Underpinning in Soil and Excavation Support

Appendices

Appendix A	Borehole Records
Appendix B	Geotechnical Laboratory Test Results
Appendix C	Certificate of Analysis



Acronyms and Abbreviations

AST	Aboveground Storage Tank
the City	The City of Ottawa
km	Kilometre
L	Litre
m	Metre
m ²	Square Metre
m amsl	Metres Above Mean Sea Level
mbgs	Metres Below Ground Surface
mm	Millimetre
MOE	Ministry of the Environment
MECP	Ontario Ministry of the Environment, Conservation, and Parks
O.Reg.	Ontario Regulation
SLR	SLR Consulting (Canada) Ltd.
TSSA	Technical Standards and Safety Authority
UST	Underground Storage Tank



1.0 Introduction

SLR Consulting (Canada) Ltd. (SLR) was retained by Suncor Energy Products Partnership (Suncor) to provide geotechnical services to support a City of Ottawa Permit application for a proposed redevelopment of an existing gas station site, located in Ottawa, Ontario.

SLR has completed a combined geotechnical and environmental site investigation to collect information for both the geotechnical Investigation and Phase II ESA. This report presents the geotechnical site investigation and laboratory testing program to be used to provide recommendations in support of the planned redevelopment of the Petro Canada Service Station property located at 6250 Hazeldean Road, Stittsville in Ottawa, Ontario (the Property).

The Geotechnical Investigation and report have been completed in accordance with SLR's work plan, dated November 2025. This report is limited to the geotechnical scope of services and the environmental aspects of SLR's services are provided under a separate cover.

2.0 Project Understanding

The Site is located at 6250 Hazeldean Road in Ottawa, Ontario, as shown in Figure 1 and Figure 2. The current property is occupied by a retail fuel outlet that consists of a pump island, car wash, kiosk and underground facilities including underground storage tank and the associated underground product piping.

SLR understands that Suncor plans to complete a site re-development for consisting of a kiosk expansion to accommodate a restaurant, interior renovations of the kiosk, repaving to incorporate a drive thru lane for the restaurant, and installation of underground Earthbins for garbage and recycling. The proposed site layout for the re-development is shown in Figure 3.

3.0 Scope of Work

The geotechnical scope of work includes geotechnical field investigation, laboratory testing, data analysis, and geotechnical recommendation for the proposed re-development.

Geotechnical laboratory testing was performed by a CCIL certified laboratory. The geotechnical laboratory analyses include natural water content, particle size distribution, Atterberg Limits, corrosivity testing (sulfate, chloride, and pH) and resistivity testing on select samples.

This geotechnical report summarizing the Geotechnical Investigation, laboratory testing, and necessary geotechnical recommendations related to the proposed redevelopment.

4.0 Field Investigation

4.1 Drilling Investigation

Prior to the field investigation, SLR personnel completed a site-specific health and safety plan for the investigation, reviewed available utility drawings and obtained public utility clearance through the Ontario One-Call program. A third-party private utility search was also completed at each of the borehole locations. Hydrovac excavations were also completed between December 4 and 9, 2025, by Super Sucker at all the borehole locations to a depth of about 2.4 metres below ground surface (mbgs) to clear locations of underground utilities prior to drilling. Strata Drilling Group (Strata)an MECP licensed drilling contractor, was retained to undertake drilling activities at the Site between January 6 to 14, 2026.



The field investigations consisted of drilling five (5) boreholes for geotechnical/environmental purposes (denoted herein as boreholes BH25-02, BH25-03 (also denoted as MW25-03), BH25-06, BH25-08, and BH25-09 (also denoted as MW25-09)). It is noted that an additional five (5) boreholes (BH25-01 (also denoted as MW25-01), BH25-04 (also denoted as MW25-04), BH25-05 (also denoted as MW25-05), BH25-07 (also denoted as MW25-07), and BH25-10) were also completed for the Phase II ESA investigation; however, these boreholes are not being considered for the geotechnical investigation. The boreholes were advanced through the hydrovac excavations, utilizing a Geoprobe 7822DT equipped with an automatic SPT hammer. SLR staff were on site to observe and record the subsurface soil and groundwater conditions at each borehole, monitor the Standard Penetration Testing (SPT) method (ASTM D 1586), and collect representative samples.

The boreholes were positioned at the approximate locations shown in Figure 2. A summary of the coordinates and drill depths for the completed boreholes is provided in Table 1.

Table 1: Summary of Boreholes

Borehole No.	Easting ¹ (m)	Northing ¹ (m)	Final Depth (mbgs) ²	Ground Surface Elevation (masl) ³
BH25-02	348886.3	5014349.5	5.0	125.0
BH25-03	348865.1	5014353.7	7.6	125.1
BH25-06	348888.8	5014400.2	2.8	124.4
BH25-08	348915.1	5014376.9	8.8	124.9
BH25-09	348918.0	5014368.1	8.9	125.2

Notes:

¹ GPS device coordinates were collected by J.D. Barnes on January 26, 2025. Datum of coordinates is MTM Zone 9 CSRS 2010.

²mbgs - meter below ground surface

³masl - meter above sea level

As part of the investigation, disturbed soil samples (grab samples) were collected from the side wall of the hydrovac holes using a sample collector, and from the SPT split spoon sampler during drilling.

In-situ testing comprising of SPTs were conducted at select depths at each borehole. A 24" (609 mm) long split spoon sampler was used. The number of blows to push the sampler into the soil over four 0.15 m increments were recorded and the first increment was neglected and the sum of blows over the second and third increments was recorded as the SPT-N value, which is shown on the Borehole Record sheets in Appendix A.

In cases, where the sampler did not advance a full 0.15 m increment within 50 blows, the depth of advance was recorded, and the test was considered to have reached practical refusal and testing was stopped to prevent damage to equipment.

The depths and results of the SPT's, sample types and depths, and subsurface descriptions are provided in the Borehole Record sheets provided in Appendix A.



4.2 Laboratory Testing

Laboratory testing included water content, particle size analysis, Atterberg Limits, and corrosivity (sulphate, chloride, and pH) testing, and resistivity testing on select samples. The laboratory test results are provided in Appendix B and are annotated on the Borehole Record sheets provided in Appendix A. The analytical data is provided as part of the Laboratory Certificate of Analysis in Appendix C.

A summary of the particle size analysis, and corrosivity test and resistivity test results is provided in Table 2 and Table 3 respectively.

Table 2: Summary of Particle Size Analysis Testing

Borehole No.	Sample No.	Depth (mbgs)	Particle Size Distribution (%)			
			Gravel	Sand	Fines	
					Silt	Clay
BH25-02	SS1	2.4 ~ 3.1	0	82.5	4.2	3.3
BH25-03	SS1	2.4 ~ 3.0	9.3	78.2	8.4	4.1
BH25-06	SS4	2.3 ~ 2.8	32.2	52.9	10.7	4.2
BH25-08	SS9	7.6 ~ 8.2	0.6	83	13.5	2.9
BH25-09	SS6	6.1 ~ 6.2	12.7	75.7	9.6	2

Table 3: Summary of Corrosivity (Sulfate, Chloride, pH and Resistivity) Testing

Borehole No.	Sample No.	Depth (mbgs)	SO ₄ Sulfate (mg/kg)	Chloride (mg/kg)	pH	Resistivity (Ohm-cm)
BH25-08	SS4	2.3 ~ 2.9	28	107	8.16	3370
BH25-09	SS5	5.3 ~ 5.4	<20	<5.0	8.05	10500

5.0 Subsurface Conditions

5.1 Site and Regional Geology

The Site is situated within the Ottawa Valley Clay Plains physiographic region of Southern Ontario (Chapman and Putnam, 1984). The physiographic landform of the site is comprised of sand plains (Chapman and Putnam, 1984).

A review of available Ontario surficial geology mapping indicated that the overburden materials of the site is generally comprised of glaciofluvial deposits consisting of river deposits and delta topset facies. Bedrock geology mapping indicates that the Site is underlain by bedrock comprised of limestone, dolostone, shale, arkose, and sandstone of the Ottawa Group (Ontario Geological Survey, 2011).

5.2 Soil Conditions

The soil descriptions provided in this report are based on accepted standard methods of classification and identification routinely used in current geotechnical standards of practice.



The subsurface conditions encountered in each of the boreholes are presented on the Borehole Record sheets provided in Appendix A. The stratigraphic boundaries shown on the Borehole Records are inferred from observations made during drilling and represent transitions between soil types rather than exact planes of geological changes.

5.2.1 Topsoil

An 80 to 150 mm thick layer of surficial topsoil was encountered at Boreholes BH25-08 and BH25-09. It should be noted that the thickness of the topsoil explored at the borehole locations may not be representative for the site and should not be relied on to calculate the amount of topsoil at the site.

5.2.2 Pavement Structure

Pavement structure was encountered at the surface of Boreholes BH25-02, BH25-03, and BH25-06. The existing pavement structure encountered from these boreholes are summarized in Table 4.

Table 4: Existing Pavement Structure

Borehole No.	Thickness of Pavement Structure		
	Asphalt (mm)	Granular Base / Subbase (mm) ¹	Total (mm)
BH25-02	80	180	260
BH25-03	80	180	260
BH25-06	80	80	160

Notes:
¹ Thickness of granular base / subbase is to be considered approximate based on observation during daylighting.

5.2.3 Fill Materials

Fill materials consisting of sand and gravel, silty sand, gravelly sand, and sand were encountered below the pavement structure in all boreholes. Fill materials extended to depths ranging from about 1.5 to 2.8 m below existing ground surface (Elevation 123.4 to 121.7 m). Borehole BH25-06 was terminated in these deposits. For the cohesionless fill materials, a SPT 'N' value of 0 to greater than 50 blows per 300 mm penetration indicated very loose to very dense compactness condition. The in-situ moisture contents measured in the fill samples ranged from approximately 2% to 12%.

5.2.4 Sand

Sand deposits were encountered beneath the fill materials in all boreholes and extended to depths ranging from 5.0 to 8.9 m below existing ground surface (Elevation 119.9 to 116.0 m). Boreholes BH25-02, BH25-03, BH25-08, and BH25-09 were terminated in these deposits. SPT 'N' values ranging from 19 to greater than 50 blows per 300 mm penetration indicated compact to very dense compactness condition. The natural moisture contents measured in the soil samples ranged from approximately 3% to 71%.



5.3 Groundwater

Groundwater level measurements were taken from each of the installed monitoring wells during a visit on January 26, 2026. The measured groundwater levels ranged from about 5.0 to 7.7 m below ground surface. A summary of the groundwater level measurements is provided in Table 5.

Table 5: Summary of Groundwater Level Readings

Borehole No.	Screened Interval (mbgs) ¹	Groundwater Depth (mbgs) ¹ / Groundwater Elevation (masl) ²
		January 26, 2026
BH25-03	3.4 ~ 6.4	120.0 / 5.0
BH25-09	5.8 ~ 8.8	117.5 / 7.7
Notes: ¹ mbgs - meter below ground surface ² masl - meter above sea level		

It should be noted that groundwater levels can be expected to seasonally fluctuate from higher to lower elevation depending on precipitation, runoff conditions and other salient factors.

6.0 Geotechnical Investigation and Recommendations

SLR understands that Suncor plans to complete a site re-development consisting of expanding the kiosk building, interior renovations of the kiosk, repaving to incorporate a drive thru lane for the restaurant, and installation of underground Earthbins for garbage and recycling.

The geotechnical investigation and general recommendations for the design and construction of the proposed site re-development are as follows:

- The subsurface conditions are considered suitable for the installation of the proposed Earthbins and new pavements structure.
- The subsurface conditions are considered suitable for shallow foundation support of proposed new infrastructure, which is assumed to comprise of relatively light loads.
- The site is also suitable for grade supported features such as slab-on-grade, thickened edge slabs and raft foundations. This report will cover floor slab design. Slab-on-grade design, thickened edge slab, and raft foundations recommendations can be provided at a later date should Suncor require these design elements.
- Measurement from installed monitoring wells indicated groundwater at depth (i.e., within about 5.0 to 7.7 m below existing ground surface).
 - Temporary dewatering, such as pumping from temporary sumps or other means as may be required to control inflow of water from granular subsurface soils for excavations below the groundwater level.
 - Design of subsurface structures below the groundwater table to consider hydrostatic forces or installation of permanent groundwater control (i.e., drainage) measures, and buoyancy effects for below grade structures, as may be required.



The geotechnical recommendations provided are intended for the guidance of the design engineer. Where comments are made on construction, they are provided to highlight aspects of construction that could affect the design of the project and constructability from a geotechnical perspective. Those requiring information on aspects of the site beyond the scope of this report must make their own interpretation of the information provided.

6.1 Geotechnical Parameters

Based on the results of the field investigation and experience with similar soils, estimated geotechnical soil parameters are provided in Table 6.



Table 6: Estimated Geotechnical Soil Parameters

Soil Type	New Granular Fill		Existing Fill	Non-Cohesive Native Soils – Gravelly Sand, Sand, Silty Sand (Till) / Sandy Silt (Till), Silt						Cohesive Native Soil – Clayey Silt (Till) / Silty Clay (Till)				
	'A'	'B'		4-50	5-10	11-14	15-29	30-39	40-50	>50	3-9	10-14	15-29	30-50
SPT 'N'														
Unit weight (kN/m ³)	22	21	19	19	20	21	21.5	22	22.5	19	20.5	21	21.5	22.5
Effective angle of internal friction (°), ϕ'	35	32	24	26	28	30	32	34	37	26	28	30	32	34
Effective cohesion, c' (kPa)	-	-	-	-	-	-	-	-	-	0	2	5	10	10
Undrained shear strength (kPa)	-	-	-	-	-	-	-	-	-	40	70	100	200	300
Coefficient of lateral earth pressure														
Active, K_a	0.27	0.31	0.42	0.39	0.36	0.33	0.31	0.28	0.25	0.39	0.36	0.33	0.31	0.28
At rest, K_o	0.43	0.47	0.59	0.56	0.53	0.50	0.55	0.60	0.80	0.56	0.53	0.50	0.60	1.00
Passive, K_p	3.69	3.25	2.37	2.56	2.77	3.00	3.25	3.54	4.03	2.56	2.77	3.00	3.25	3.54
Elastic modulus (MPa)	-	-	-	5	6.3	8	30	40	50	4	8	15	30	50
Poisson's ratio	-	-	-	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Modulus of subgrade reaction, k (MN/m ³) (*)	-	-	-	5/B	6.3/B	8/B	30/B	40/B	50/B	4/B	8/B	15/B	30/B	50/B
Lateral modulus of subgrade reaction, K_h (MN/m ³) (*)	-	-	-	5/B	6.3/B	8/B	30/B	40/B	50/B	4/B	8/B	15/B	30/B	50/B
Note: * B is the width of footing or width of wall/pile in metres.														



6.2 Shallow Foundations for Kiosk Expansion

The following recommendations are made for shallow foundations:

- Ensure the founding stratum is on the existing undisturbed compact to very dense sand.
- The existing fill materials along with loose native soils are considered unsuitable as the base for shallow foundations. These soils will require excavation to a depth of 1 m below the foundation level and backfilled with engineered granular fill material compacted to 100% of SPMDD (standard proctor maximum dry density) to the foundation level.
- Ensure the footings are founded below the depth of frost penetration. Once the contractor is satisfied that bearing surface has been prepared, SLR geotechnical personnel should be contacted and should inspect all footing bearing surfaces prior to pouring the footing.
- Should smaller areas of over-excavation be necessary, backfill the over-excavation with a lean concrete mixture.
- Shallow foundations should have a minimum width of 450 mm and must be adequately reinforced to distribute the applied loads and have sufficient stiffness to distribute local overstresses.
- Perimeter insulation may be required for unheated structures if footings are shallower than the frost depth. An adfreeze strength of 65 kPa between soil and concrete may be used to estimate the uplift forces on shallow foundations during freezing conditions.
- For the kiosk expansion the geotechnical unfactored bearing resistance at Ultimate Limit States (ULS) and Serviceability Limit State (SLS) for design foundations bearing on suitably compacted controlled engineered fill or native soils are provided in Table 7, placed below frost depth. Foundations designed to the specified bearing capacity at SLS are expected to settle less than 25 mm total and 19 mm differential.

Table 7: Bearing Values for Kiosk Expansion

Borehole	Anticipated Founding Material	Bearing Capacity at SLS (kPa)	Factored Geotechnical Resistance at ULS (kPa)	Anticipated Founding Depth (mbgs) ¹ / Elevation (m)
BH25-08	Sand	100	150	1.8 / 123.1
BH25-09	Sand	100	150	3.2 / 122.1
Note: ¹ mbgs - meter below ground surface				

Shallow foundations should be supported on at least 150 mm of compacted, freely draining, well graded 19 mm minus crushed gravel base course, placed over competent subgrade soils. The compacted base course material should be uniformly compacted to at least 100% Standard Proctor Maximum Dry Density (SPMDD, as per ASTM D698). It is recommended that qualified geotechnical personnel review final footing design, subgrade conditions, and foundation preparation prior to placing concrete to confirm that the ground conditions are as described in this report.



The excavated footing bases can be covered with 50 mm thick lean concrete slab immediately after inspection and cleaning in order to avoid disturbance of the founding soil due to water, construction activity and weathering/drying.

In the vicinity of the existing buried utilities, all footings must be lowered to undisturbed native soils, or alternatively the services must be structurally bridged. Where it is necessary to place footings at different levels, the upper footing must be founded below an imaginary 10 horizontal to 7 vertical line drawn up from the base of the lower footing. The lower footing must be installed first to help minimize the risk of undermining the upper footing.

6.3 Floor Slab

The existing fills are considered not suitable for supporting the floor slab. The floor slab can be supported on grade provided all existing fill, and weak or disturbed soils are removed, and the base thoroughly proof rolled. Any soft spots revealed during proof rolling must be sub-excavated and backfilled. The backfill required to raise the grade can consist of inorganic soil, placed in shallow lifts (200 mm) and compacted to 98% of Standard Proctor Maximum Dry Density (SPMDD).

A moisture barrier consisting of at least 200 mm of 19 mm clear crushed stone should be installed under the floor slab.

Special care should be taken to ensure compaction around columns and adjacent to foundation walls. Unless the foundations are designed to account for the floor slab loads, the floor slabs should be structurally separated from the foundation walls and columns. Sawcut control joints should be provided at regular intervals and along column lines to minimize shrinkage cracking and to allow for differential settlement of the floor slabs.

Where the backfill against the exterior walls is to support settlement sensitive structures, such as concrete slabs, pavements or walkways, it should be uniformly compacted to at least 98% of SPMDD.

6.4 Earthbins

6.4.1 Support and Bedding

All topsoil, fill materials, and disturbed or other unsuitable material must be removed from excavation base prior to placement of earthbin bedding.

The borehole information indicates that the native soils encountered at the site are capable of providing adequate support for the earthbin using conventional granular bedding.

The recommended minimum thickness of granular bedding below the footing of the earthbin is 300 mm where the subgrade consists of competent native soils.

Where the fill or otherwise unsuitable soils are present at the proposed earthbin footing elevation, the unsuitable materials should be sub-excavated and replaced using conventional granular bedding. In this case, the recommended minimum thickness of granular bedding below the invert of the Earthbin is 300 mm. Geotechnical inspection is required to confirm suitable founding conditions.

The compacted granular base material for the earthbin should consist of OPSS 1010 Granular "A" type material. All granular materials should be placed in loose lifts of 150 mm thickness and then compacted.



The granular bedding materials should be compacted to 100% of Standard Proctor Maximum Dry Density (SPMDD) at a placement water content within $\pm 2\%$ of the materials optimum.

6.4.2 Bearing Resistance

If required, footings for the earthbins may be founded on the native undisturbed compact to dense sand and can use an allowable (SLS) bearing resistance of 100 kPa and a factored ULS bearing resistance of 150 kPa. Structures designed to the specified bearing resistance at SLS are expected to settle less than 25 mm total and 19 mm differential.

6.5 Frost Protection Recommendations

All footings exposed to seasonal freezing conditions must have at least 1.8 metres of soil cover for frost protection.

If soil cover is not possible, a 25 mm thick layer of polystyrene insulation is thermally equivalent to 600 mm of soil cover. It is also emphasized that underfloor drainage and/or an adequate free draining gravel base is required to minimize the risk of floor dampness. Floor dampness could lead to temporary icing and the risk of accidents.

6.6 Lateral Earth Pressure

The lateral earth pressure acting on the permanent rigid walls of the underground structures in overburden soils can be evaluated by the following formula:

$$P_h = K (\gamma h + q)$$

- where P_h = Lateral earth pressure acting at depth "h" (kPa)
 K = Earth pressure coefficient at rest for a horizontal ground surface condition, as shown in Table 6
 γ = Unit weight of backfill, as shown in Table 6
 h = Depth below finished grade of the point of interest (m)
 q = Equivalent value of surcharge on the ground surface (kPa)

If there is no provision for drainage of the backfill behind the subsurface walls, the walls should be designed to resist the lateral earth pressure and the hydrostatic pressure imposed by the backfill adjacent to the wall.

Below the water table, the submerged unit weight of the soil should be used and the full hydrostatic water pressure from ground surface should be added. If the ground surface is not horizontal, the uneven portion can be treated as an equivalent surcharge load.

6.7 Excavation and Backfilling

According to the results of this investigation, the excavations are generally anticipated to be carried out in the fill materials and native sand deposits. This excavation can be carried out with heavy hydraulic backhoe.

Possible large obstructions such as buried concrete pieces and existing foundations may also be encountered at the Site within the fill materials. Provisions must be made in the excavation contract for the removal of possible boulders in the till or obstructions in the fill material.



All excavations must be carried out in accordance with the most recent Occupational Health and Safety Act (OHSA). In accordance with OHSA, the fill materials and native sand would be classified as Type 3 Soils above the groundwater table and Type 4 soils below the groundwater table.

It may be necessary to flatten the excavation slopes if seepage zones or loose/soft conditions are encountered locally. Excavations should be continuously examined for any evidence of instability if left open for extended periods of time or following weather events such as rain or freeze/thaw.

It is anticipated that foundation excavations at the site will consist of temporary open cuts with side slopes not steeper than 1.5 horizontal to 1 vertical (1.5H:1V). However, depending on the construction procedures adopted by the contractor and weather conditions at the time of construction, some local flattening of the slopes might be required. Where side slopes of excavations are to be steepened, then a temporary excavation support system such as steel sheeting will be required.

Vertical cuts in any of the soil types and over-steepened slopes should be supported with shoring and bracing to safeguard the stability of the sides of the excavation.

The existing fill in the boreholes is generally not suitable for re-use as backfill. The native soils free from topsoil and organics can be used as general construction backfill. The suitability for reuse of the native soils is further discussed in Section 6.11. Loose lifts of soil, which are to be compacted, should not exceed 200 mm. Depending on the time of construction and weather, some excavated material may be too wet to compact and will require aeration prior to its use.

Under floor fill should be compacted to at least 98% of Standard Proctor Maximum Dry Density (SPMDD). The excavated soils are not considered to be free draining. Where free draining backfill is required, imported granular fill such as OPSS Granular "B" should be used. Imported granular fill, which can be compacted with handheld equipment, should be used in confined areas.

It should be noted that the excavated soils are subject to moisture content increase during wet weather which would make these materials too wet for adequate compaction. Stockpiles should be compacted at the surface or be covered with tarpaulins to minimize moisture uptake.

It is expected that any seepage above the groundwater table can be removed by pumping from sumps in the building development area. Depending upon the actual thickness and extent of the sandy fill and native sandy soils, the prevailing groundwater level at the time of construction, "active, advance" dewatering measure using well points/eductors may be required to maintain the stability of the base and side slopes of the excavations in these areas. These 'active dewatering' measures would have to be installed and then operated for one to two weeks in advance of excavation work progressing to these areas. A contractor specializing in dewatering should be retained to design the active dewatering systems.

It should be noted that if the construction dewatering system/sumps result in a water taking of more than 50,000 L/day, a registration should be made in the Environmental Activity and Sector Registry (EASR).

6.8 Seismic Site Classification

The 2012 Ontario Building Code (OBC 2012) came into effect on January 1, 2014, and contains updated seismic analysis and design methodology. The seismic site classification methodology outlined in the code is based on the subsurface conditions within the upper 30 m below existing grade.



The conservative site classification is based on physical borehole information obtained at depths of less than 30 m and based on general knowledge of the local geology and physiography. In this regard, SLR’s drilling program included boreholes drilled to depths up to 8.9 m below the existing ground surface. Based on the borehole information and our local experience, a Site Class C may be used for the design for this site.

Should optimization of the site class be recommended by the structural engineer, a field seismic shear wave velocity test should be considered to confirm the classification.

6.9 Proof Rolling

Upon completion of initial site preparation activities (as discussed above), proof rolling of the subgrade should be conducted to verify that competent and uniform soil subgrade support conditions have been achieved. Proof rolling should not be conducted during or shortly following precipitation events, and heavy equipment shall not be allowed to travel on wet/soft subgrade soils until adequate drying has occurred. Proof rolling should be performed by two passes of a dual-wheel truck (or comparable equipment) with a minimum of 80 kN single axle load. Soils which display rutting or appreciable deflections upon proof-rolling should be over-excavated to expose more competent soil and replaced with suitable engineered fill. Alternately, the use of geosynthetics (woven geotextile, geogrid in conjunction with non-woven geotextile, or combination geotextile/geogrid products), possibly in conjunction with some over-excavation, may be an alternative. If geosynthetics are utilized, it is recommended that granular fill materials be placed directly over the geosynthetics. The geosynthetics should be placed in accordance with the manufacturer’s recommendations. Construction techniques should be designed to minimize the potential for damage to the geosynthetics and underlying subgrade soils (i.e., end-dump and spread methods, use of long reach and/or low contact pressure equipment, etc.). SLR should be retained to provide guidance with respect to subgrade improvement measures.

Following efforts to stabilize the soil, proof rolling should be repeated. All proof rolling and compaction efforts should include documentation detailing the findings, including photographs where possible.

6.10 Pavement Design

The structural thickness recommendations herein were designed using the AASHTO 1993 Pavement Design Guide. The design used an overall standard deviation of 0.45, a loss of serviceability of 1.7 (initial serviceability of 4.2 and a terminal serviceability of 2.5), a drainage coefficient of 1.0 and a reliability of 85%. The structural layer coefficients (a_i) and drainage coefficients (m_i) used to determine the geotechnical design thickness are shown in Table 8 which are in accordance with the Ontario Ministry of Transportation and Infrastructure.

Table 8: AASHTO 1993 Pavement Design Parameters

Material Description	Structural Layer Coefficient [a_i]	Drainage Coefficient [m_i]
Asphalt Concrete Pavement (ACP)	0.40	-
Base Course Gravel	0.14	0.95
Prepared Sand and Gravel Subgrade	0.10	0.95



Based on the existing pavement thickness and subsurface conditions encountered at the boreholes, the recommended pavement structure for light (i.e. passenger vehicles) and limited heavy duty (infrequent delivery, garbage, fuel truck loading) traffic loading with assumed maximum equivalent single axle load (ESAL's) as shown below, is provided in Table 9.

Table 9: Pavement Structure

Pavement Layer	Compaction Requirements	Thickness or Strength requirement for Maximum 1×10^5 ESAL's [mm]
HL 3 - Surface Course Asphalt	93% MRD (Maximum Relative Density)	40
HL 8 Binder Course Asphalt		80
OPSS Granular "A" Base (or 20mm Crusher Run Limestone)	100% SPMDD*	150
OPSS Granular "B" (or 50mm Crusher Run Limestone)	100% SPMDD	450
Total	--	720
Subgrade	--	Mr = 35 MPa

The pavement structure assumes that the construction will be completed at a drier time of year and the subgrade is stable. If the subgrade becomes wet or rutted during construction activities additional subbase may be required. The subgrade must be compacted to 98% SPMDD for at least the upper 500 mm unless accepted by SLR.

It is recommended that qualified SLR personnel conduct an inspection of excavated areas. Use a nonwoven geotextile on the surface of the subgrade if areas of concern be identified and finish to a tight, smooth surface that is free from ruts, waves, and roller marks.

The long-term performance of the pavement structure is highly dependent upon the subgrade support conditions. Stringent construction control procedures should be maintained to ensure uniform subgrade moisture and density conditions are achieved. In addition, the need for adequate drainage cannot be over-emphasized. The finished pavement surface and underlying subgrade should be free of depressions and should be sloped (preferably at a minimum grade of two percent) to provide effective surface drainage toward catch basins. Surface water should not be allowed to pond adjacent to the outside edges of pavement areas. Subdrains should be installed to intercept excess subsurface moisture and prevent subgrade softening.

This is particularly important in heavy-duty pavement areas.

Additional comments on the construction of access road, internal roadways and parking areas are as follows:

- 1 As part of the subgrade preparation, proposed parking areas and access roadways should be stripped of topsoil, fill materials, weak native soils, and other obvious objectionable material. Fill required to raise the grades to design elevations should conform to backfill requirements outlined in previous sections of this report. The subgrade should be properly shaped, crowned then proof-rolled in the full-time presence of a qualified engineering personnel. Soft or spongy subgrade areas should be sub-excavated and properly replaced with suitable approved backfill compacted to 98% SPMDD.



- 2 The locations and extent of sub-drainage required within the paved areas should be reviewed by this office in conjunction with the proposed lot grading. Assuming that satisfactory crossfalls in the order of two percent have been provided, subdrains extending from and between catch basins may be satisfactory. In the event that shallower crossfalls are considered, a more extensive system of sub-drainage may be necessary and should be reviewed by a specialized pavement engineer.

The most severe loading conditions on light-duty pavement areas and the subgrade may occur during construction. Consequently, special provisions such as restricted access lanes, half-loads during paving, etc., may be required, especially if construction is carried out during unfavourable weather.

6.11 Geotechnical Quality of Excavated Soils

Reference to the borehole logs suggests that the excavated materials with respect to their compaction characteristics can be divided into three groups:

- **Group 1** comprises the pavement granular base/subbase materials encountered near the surface, and sand soils. These materials are expected to have good compaction characteristics and could be reused as construction backfill provided that they are carefully segregated from the more silty or clayey soil strata. Some drying of the sand will likely be required. There are limited quantities of these materials available.
- **Group 2** comprise the cohesionless to low plasticity sand. The compaction of these soils will require a very tight control of their moisture content during placement and compaction. At moisture contents more than 3% below the optimum, the soil will likely be dusty and “flour” like while at moisture contents $\pm 1\%$ higher than optimum, the soil will be “spongy” and will “pump”.
- **Group 3** soils consist of unsuitable materials because of their high moisture or organic inclusions, including all existing fill materials. These soils should be either disposed off-site or should be used only in “soft” landscaping areas where they can be placed with nominal compaction, and where surface settlements are tolerable. If soils are disposed of off-site, a qualified person should ensure disposal is in compliance with O.Reg 406/19 (excess soil management).

As a general requirement, all backfill material should be placed in 200 to 300mm thick loose lifts and compacted to at least 96% of SPMDD, at a placement moisture content within $\pm 2\%$ of the optimum. Below future pavements, the backfill must be Granular “A” or “B” material, and the top 1.5m of subgrade backfill below the underside of the pavement structure should be compacted to 98% of SPMDD. Where a free-draining backfill is needed or where the backfill is needed for structural support of overlying structures, the site soils will not be suitable and OPSS Granular “A” or “B” sand and gravel will be required. Similarly, during work in the autumn, winter and spring months, re-use of the excavated soils as compacted fill may not be practical and imported OPSS Granular “B” should be used.

6.12 Preconstruction Condition Survey

It is recommended that a preconstruction survey of neighboring properties and any adjacent utilities and structures be completed prior to excavation and throughout the construction period.

Additionally, the types and condition of all adjacent structures and underground services should be reviewed by the structural and geotechnical engineer to determine potential underpinning requirements as conceptually identified in Figure 4.



Utility owners should be contacted to establish deformation limits. The deformation should be monitored throughout the construction period.

6.13 Field Review and Quality Control

It is recommended that geotechnical field reviews be carried out to assess the actual soil conditions encountered and confirm assumptions used in the design. Where conditions encountered differ significantly from those assumed for design, SLR should be provided with an opportunity to review the design assumptions and modify the design, as appropriate. Field reviews should include review of footing excavations and quality control testing carried out to assess conformity with design.

In order to provide Ontario Building Code Letters of Assurance, SLR personnel must review the work during various stages of construction which includes but is not limited to subgrade excavation and preparation, excavated slopes and temporary shoring or trenching activities, placement and compaction of fill, and implementation of any drainage measures. SLR must be notified at least 24 hours in advance when the work is ready for field review and inspection.

7.0 Closure


We trust the above information meets your current requirements. Please contact the undersigned if there are any questions.

Regards,

SLR Consulting (Canada) Ltd.



Iqbal Budwal, M.Sc., P.Eng.
Geotechnical Engineer



Matthew D. St Denis, P.Eng.
Team Lead, Geotechnical Engineering East



8.0 References

- ASTM International. 2018. *ASTM D1586 / D1586M-18, Standard test method for standard penetration test (SPT) and split-barrel sampling of soils.*
- Canadian Geotechnical Society;. 2023. *Canadian Foundation Engineering Manual, 5th Edition.*
- Chapman, L.J. and Putnam, D.F. 1984. *Physiography of southern Ontario; Ontario Geological Survey.*
- Environment and Natural Resources. 2020. *Government of Canada.* July 22.
https://climate.weather.gc.ca/climate_normals/index_e.html.
- Ontario Geological Survey. 2011. "1:250 000 scale bedrock geology of Ontario; Ontario Geological Survey, Miscellaneous Release---Data 126-Revision 1."
- Ontario Geological Survey. 2010. "Surficial geology of southern Ontario; Ontario Geological Survey, Miscellaneous Release— Data 128 – Revised."





Figures



Geotechnical Investigation for Pre-Construction Support of Future Development

Active Petro-Canada Retail Fuel Outlet No. 65044 6250 Hazeldean Rd, Ottawa, Ontario

Suncor Energy Products Partnership

SLR Project No.: 216.030133.00001

March 11, 2026



NOTES:
NOT A LEGAL SURVEY. DO NOT USE FOR CONSTRUCTION.


REFERENCED FROM: K PAUL ARCHITECT INC., PROJECT No. 655044, DRAWING No. SP1, DATE 2025-09-04 AND SITE RECONNAISSANCE INFORMATION.

IMAGERY: ESRI, VANTOR, EARTHSTAR GEOGRAPHICS, AND THE GIS USER COMMUNITY (IMAGE DATE: MAY 8, 2022)

BASEDATA:
ESRI, HERE, GARMIN, INTERMAP, INCREMENT P CORP., GEBCO, USGS, FAO, NPS, NRCAN, GEOBASE, IGN, KADASTER NL, ORDNANCE SURVEY, ESRI JAPAN, METI, ESRI CHINA (HONG KONG), © OPENSTREETMAP CONTRIBUTORS, AND THE GIS USER COMMUNITY

LEGEND:

- — — — — PROPERTY BOUNDARY
- ▭ SITE BOUNDARY
- - - - - PHASE 1 STUDY AREA



SUNCOR ENERGY PRODUCTS PARTNERSHIP
OUTLET NO. 65044
6250 HAZELDEAN ROAD
STITTSVILLE, ON

GEOTECHNICAL INVESTIGATION


**SITE LOCATION
AND SURROUNDING LAND USE**

SLR FIGURE NO:
1



- LEGEND:**
- SITE BOUNDARY
 - ⊕ BOREHOLE
 - ⊙ MONITORING WELL
 - UTILITIES AND SYMBOLS**
 - CB CATCH BASIN
 - T TRANSFORMER

NOTES:
 NOT A LEGAL SURVEY. DO NOT USE FOR CONSTRUCTION.
 REFERENCED FROM: K PAUL ARCHITECT INC., PROJECT No. 655044,
 DRAWING No. SP1, DATE 2025-09-04 AND SITE RECONNAISSANCE
 INFORMATION.
 IMAGERY: ESRI, VANTOR, EARTHSTAR GEOGRAPHICS, AND THE GIS
 USER COMMUNITY (IMAGE DATE: MAY 27, 2025)





SUNCOR ENERGY PRODUCTS PARTNERSHIP
 OUTLET NO. 65044
 6250 HAZELDEAN ROAD
 STITTSVILLE, ON

GEOTECHNICAL INVESTIGATION

SITE PLAN AND SAMPLING LOCATIONS

SLR FIGURE NO:
2



**PART OF THE WEST 1/2 LOT 23
CONCESSION 12
GEOGRAPHIC TOWNSHIP OF GOULBOURN
CITY OF OTTAWA**

- LEGEND**
- EXISTING CAR WASH AREA
119.2 M²
1,283.3 FT²
 - EXISTING C-STORE AREA
119.4 M²
1,285 FT²
 - ADDITION RESTAURANT AREA
128.3 M²
1,388.8 FT²

NO.	DATE	DESCRIPTION
01	MM/DD/YY	ISSUED FOR CLIENT REVIEW

NO.	DATE	DESCRIPTION

SEAL

The contractor will check and verify dimensions and report errors and omissions to the designer and the design professional whose seal is affixed to this drawing. Do not make the drawings.
This drawing will not be used for construction purposes until issued for construction by the design professional whose seal is affixed to this drawing and whose signature is below.

ISSUED FOR CONSTRUCTION _____ DATE _____
DIMENSIONS AND CONDITIONS TO BE VERIFIED ON THE PREMISES

PAUL ARCHITECT INC.
TORONTO • VANCOUVER • ORLANDO

3400 Sheppard Avenue, Dr. Suite 200, Oakville, Ontario, L4J 7Y8
www.paularchitect.com
(905) 337-9900 Fax: (905) 337-1986




DRAWING TITLE
PROPOSED SITE PLAN

PROJECT
6250 HAZELDEAN ROAD & CARP ROAD
STITTSVILLE, ON

DRAWN F. EMMANUEL	CHECKED
SCALE 1:200	DATE 2025-09-04
PROJECT NO. 65044	DRAWING NO. SP1

Guidelines for Underpinning in Soil and Excavation Support

Existing foundations located within Zone A normally require underpinning, especially for heavy structures. For some foundations in Zone A, it may be possible to eliminate underpinning and control foundation movement by tightly braced excavation walls, such as caisson walls.



Zone A Foundations located within this zone normally require underpinning. Horizontal and vertical pressures on the excavation wall of non underpinned foundations must be considered

Zone B Foundations located within this zone normally do not require underpinning. Horizontal and vertical pressures on the excavation wall of non underpinned foundations must be considered

Zone C Underpinning to structures is normally founded in this zone. Lateral pressure from underpinning is not normally considered

A condition survey should be conducted prior to construction and appropriate monitoring (surface and insitu) carried out during construction to monitor any movement which may occur.

All work should be carried out in accordance with the Occupational Health and Safety Act and local regulations. Good quality workmanship and construction practices are to be employed.

(Reference: Figure 20.39 from Canadian Foundation Engineering Manual, 5th Edition)



Appendix A Borehole Records

Geotechnical Investigation for Pre-Construction Support of Future Development

Active Petro-Canada Retail Fuel Outlet No. 65044 6250 Hazeldean Rd, Ottawa, Ontario


Suncor Energy Products Partnership

SLR Project No.: 216.030133.00001

March 11, 2026

Notes On Sample Descriptions

- All sample descriptions included in this report generally follow the Unified Soil Classification. Laboratory grain size analyses provided by PECG also follow the same system. Different classification systems may be used by others, such as the system by the International Society for Soil Mechanics and Foundation Engineering (ISSMFE). Please note that, with the exception of those samples where a grain size analysis and/or Atterberg Limits testing have been made, all samples are classified visually. Visual classification is not sufficiently accurate to provide exact grain sizing or precise differentiation between size classification systems.



- Fill:** Where fill is designated on the borehole log it is defined as indicated by the sample recovered during the boring process. The reader is cautioned that fills are heterogeneous in nature and variable in density or degree of compaction. The borehole description may therefore not be applicable as a general description of site fill materials. All fills should be expected to contain obstruction such as wood, large concrete pieces or subsurface basements, floors, tanks, etc., none of these may have been encountered in the boreholes. Since boreholes cannot accurately define the contents of the fill, test pits are recommended to provide supplementary information. Despite the use of test pits, the heterogeneous nature of fill will leave some ambiguity as to the exact composition of the fill. Most fills contain pockets, seams, or layers of organically contaminated soil. This organic material can result in the generation of methane gas and/or significant ongoing and future settlements. Fill at this site may have been monitored for the presence of methane gas and, if so, the results are given on the borehole logs. The monitoring process does not indicate the volume of gas that can be potentially generated nor does it pinpoint the source of the gas. These readings are to advise of the presence of gas only, and a detailed study is recommended for sites where any explosive gas/methane is detected. Some fill material may be contaminated by toxic/hazardous waste that renders it unacceptable for deposition in any but designated land fill sites; unless specifically stated the fill on this site has not been tested for contaminants that may be considered toxic or hazardous. This testing and a potential hazard study can be undertaken if requested. In most residential/commercial areas undergoing reconstruction, buried oil tanks are common and are generally not detected in a conventional preliminary geotechnical site investigation.
- Till:** The term till on the borehole logs indicates that the material originates from a geological process associated with glaciation. Because of this geological process the till must be considered heterogeneous in composition and as such may contain pockets and/or seams of material such as sand, gravel, silt or clay. Till often contains cobbles (60 to 200 mm) or boulders (over 200 mm). Contractors may therefore encounter cobbles and boulders during excavation, even if they are not indicated by the borings. It should be appreciated that normal sampling equipment cannot differentiate the size or type of any obstruction. Because of the horizontal and vertical variability of till, the sample description may be applicable to a very limited zone; caution is therefore essential when dealing with sensitive excavations or dewatering programs in till materials.

Explanation of Terms Used in the Record of Borehole

Sample Type

AS	Auger sample
BS	Block sample
CS	Chunk sample
DO	Drive open
DS	Dimension type sample
FS	Foil sample
RC	Rock core
SC	Soil core
SS	Spoon sample
ST	Slotted tube
TO	Thin-walled, open
TP	Thin-walled, piston
WS	Wash sample

Penetration Resistance

Standard Penetration Resistance (SPT), N:

The number of blows by a 63.5 kg (140 lb) hammer dropped 760 mm (30 in) required to drive a 50 mm (2 in) drive open sampler for a distance of 300 mm (12 in).

Dynamic Cone Penetration Resistance, N_d :

The number of blows by a 63.5 kg (140 lb) hammer dropped 760 mm (30 in) to drive uncased a 50 mm (2 in) diameter, 60° cone attached to "A" size drill rods for a distance of 300 mm (12 in).

Textural Classification of Soils

Classification	Particle Size
Boulders	>300 mm
Cobbles	75 mm-300 mm
Gravel (Gr)	4.75 mm-75 mm
Sand (Sa)	0.075 mm-4.75 mm
Silt (Si)	0.002 mm-0.075 mm
Clay (Cl)	<0.002 mm

Coarse Grain Soil Description (50% greater than 0.075 mm)

Terminology	Proportion
Trace	0-10%
Some	10-20%
Adjective (e.g. silty or sandy)	20-35%
And (e.g. sand and gravel)	>35%

Soil Description

a) Cohesive Soils

Consistency	Undrained Shear Strength (kPa)	SPT "N" Value
Very soft	<12	0-2
Soft	12-25	2-4
Firm	25-50	4-8
Stiff	50-100	8-15
Very stiff	100-200	15-30
Hard	>200	>30

b) Cohesionless Soils

Density Index (Relative Density)	SPT "N" Value
Very loose	<4
Loose	4-10
Compact	10-30
Dense	30-50
Very dense	>50

Soil Tests

w	Water content
w _p	Plastic limit
w _l	Liquid limit
C	Consolidation (oedometer) test
CID	Consolidated isotropically drained triaxial test
CIU	consolidated isotropically undrained triaxial test with porewater pressure measurement
D _R	Relative density (specific gravity, G _s)
DS	Direct shear test
ENV	Environmental/ chemical analysis
M	Sieve analysis for particle size
MH	Combined sieve and hydrometer (H) analysis
MPC	Modified proctor compaction test
SPC	Standard proctor compaction test
OC	Organic content test
V	Field vane (LV-laboratory vane test)
γ	Unit weight

PROJECT: Geotechnical Investigation - 6250 Hazeldean_P1,P2 & Geotec
 CLIENT: Suncor
 PROJECT LOCATION: Ottawa, ON
 DATUM: Geodetic
 BH LOCATION: See Boreholes Location Plan N 5014376.943 E 348915.123

Method: Direct Push Method/Hollow Stem Augers
 Diameter: 100mm/200mm
 Date: Jan 12, 2025
 REF. NO.: 216.030133.00001
 ENCL NO.: 4

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION	DYNAMIC CONE PENETRATION RESISTANCE PLOT				PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	POCKET PEN. (Cu) (kPa)	NATURAL UNIT WT (kN/m ³)	REMARKS AND GRAIN SIZE DISTRIBUTION (%)
(m) ELEV DEPTH	DESCRIPTION	STRATA PLOT	NUMBER	TYPE			"N" BLOWS 0.3 m	SHEAR STRENGTH (kPa)								
124.9	Ground Surface															
124.0	TOPSOIL: 80mm FILL: silty sand, trace gravel, contains rootlets, dark brown, moist, very dense to very loose.		1	SS	50/ Initial 75mm											GR SA SI CL spoon refusal on a possible boulder
123.4	SAND: trace to some silt, trace clay, trace gravel, brown, moist to wet, very dense.		2	SS	0											
123.4			3	SS	50/ 275mm											
			4	SS	63											
			5	SS	50/ Initial 100mm											Hollow Stem Augers start
			6	SS	50/ Initial 100mm											spoon refusal on a possible boulder
			7	SS	50/ Initial 125mm											spoon refusal on a possible boulder
			8	SS	50/ 125mm											
			9	SS	61											1 83 14 3
116.0	END OF BOREHOLE: 1) Upon completion of drilling the borehole was open with no groundwater accumulation.															

GROUNDWATER ELEVATIONS
 Measurement 1st 2nd 3rd 4th

GRAPH NOTES + 3, x 3: Numbers refer to Sensitivity ○ ●=3% Strain at Failure

PROJECT: Geotechnical Investigation - 6250 Hazeldean_P1,P2 & Geotec
 CLIENT: Suncor
 PROJECT LOCATION: Ottawa, ON
 DATUM: Geodetic
 BH LOCATION: See Boreholes Location Plan N 5014368.077 E 348917.986

Method: Hydrovac/Direct Push Method
 Diameter: 100mm
 Date: Jan 7, 2026

REF. NO.: 216.030133.00001
 ENCL NO.: 5

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION	DYNAMIC CONE PENETRATION RESISTANCE PLOT				POCKET PEN. (Cu) (kPa)	NATURAL UNIT WT (kN/m ³)	REMARKS AND GRAIN SIZE DISTRIBUTION (%)	
(m) ELEV DEPTH	DESCRIPTION	STRATA PLOT	NUMBER	TYPE			"N" BLOWS 0.3 m	SHEAR STRENGTH (kPa)						W _p
125.2	Ground Surface													
126.0	TOPSOIL: 150mm FILL: sand and gravel, trace silt, contains cobbles, brown, moist.		1	GS		Concrete								
0.2			2	GS										
			3	GS										
			4	GS										
			5	GS										
			1	SS	50/Initial 25mm									spoon bouncing
122.2	SAND: trace silt, trace gravel, brown, wet to moist, very dense.		2	SS	50/Initial 25mm	Bentonite								spoon bouncing
3.1			3	SS	50/Initial 25mm									spoon bouncing
			4	SS	50/Initial 25mm									spoon bouncing
			5	SS	50/Initial 75mm									spoon bouncing
			6	SS	50/Initial 100mm									spoon bouncing
			7	SS	50/Initial 25mm									spoon bouncing
			8	SS	50/Initial 50mm									spoon bouncing
116.4	END OF BOREHOLE: 1) 50mm diameter monitoring well was installed upon completion of drilling. 2) Water Level Readings: Date: Jan 26, 2026 W. L. Depth (mBGS): 7.72													Auger refusal and spoon bouncing

300 250 200 150 100 50 0
 100 200 300 400 500 600 700 800 900 1000 1100 1200 1300 1400 1500 1600 1700 1800 1900 2000 2100 2200 2300 2400 2500 2600 2700 2800 2900 3000 3100 3200 3300 3400 3500 3600 3700 3800 3900 4000 4100 4200 4300 4400 4500 4600 4700 4800 4900 5000 5100 5200 5300 5400 5500 5600 5700 5800 5900 6000 6100 6200 6300 6400 6500 6600 6700 6800 6900 7000 7100 7200 7300 7400 7500 7600 7700 7800 7900 8000 8100 8200 8300 8400 8500 8600 8700 8800 8900 9000 9100 9200 9300 9400 9500 9600 9700 9800 9900 10000 10100 10200 10300 10400 10500 10600 10700 10800 10900 11000 11100 11200 11300 11400 11500 11600 11700 11800 11900 12000 12100 12200 12300 12400 12500 12600 12700 12800 12900 13000 13100 13200 13300 13400 13500 13600 13700 13800 13900 14000 14100 14200 14300 14400 14500 14600 14700 14800 14900 15000 15100 15200 15300 15400 15500 15600 15700 15800 15900 16000 16100 16200 16300 16400 16500 16600 16700 16800 16900 17000 17100 17200 17300 17400 17500 17600 17700 17800 17900 18000 18100 18200 18300 18400 18500 18600 18700 18800 18900 19000 19100 19200 19300 19400 19500 19600 19700 19800 19900 20000 20100 20200 20300 20400 20500 20600 20700 20800 20900 21000 21100 21200 21300 21400 21500 21600 21700 21800 21900 22000 22100 22200 22300 22400 22500 22600 22700 22800 22900 23000 23100 23200 23300 23400 23500 23600 23700 23800 23900 24000 24100 24200 24300 24400 24500 24600 24700 24800 24900 25000 25100 25200 25300 25400 25500 25600 25700 25800 25900 26000 26100 26200 26300 26400 26500 26600 26700 26800 26900 27000 27100 27200 27300 27400 27500 27600 27700 27800 27900 28000 28100 28200 28300 28400 28500 28600 28700 28800 28900 29000 29100 29200 29300 29400 29500 29600 29700 29800 29900 30000 30100 30200 30300 30400 30500 30600 30700 30800 30900 31000 31100 31200 31300 31400 31500 31600 31700 31800 31900 32000 32100 32200 32300 32400 32500 32600 32700 32800 32900 33000 33100 33200 33300 33400 33500 33600 33700 33800 33900 34000 34100 34200 34300 34400 34500 34600 34700 34800 34900 35000 35100 35200 35300 35400 35500 35600 35700 35800 35900 36000 36100 36200 36300 36400 36500 36600 36700 36800 36900 37000 37100 37200 37300 37400 37500 37600 37700 37800 37900 38000 38100 38200 38300 38400 38500 38600 38700 38800 38900 39000 39100 39200 39300 39400 39500 39600 39700 39800 39900 40000 40100 40200 40300 40400 40500 40600 40700 40800 40900 41000 41100 41200 41300 41400 41500 41600 41700 41800 41900 42000 42100 42200 42300 42400 42500 42600 42700 42800 42900 43000 43100 43200 43300 43400 43500 43600 43700 43800 43900 44000 44100 44200 44300 44400 44500 44600 44700 44800 44900 45000 45100 45200 45300 45400 45500 45600 45700 45800 45900 46000 46100 46200 46300 46400 46500 46600 46700 46800 46900 47000 47100 47200 47300 47400 47500 47600 47700 47800 47900 48000 48100 48200 48300 48400 48500 48600 48700 48800 48900 49000 49100 49200 49300 49400 49500 49600 49700 49800 49900 50000 50100 50200 50300 50400 50500 50600 50700 50800 50900 51000 51100 51200 51300 51400 51500 51600 51700 51800 51900 52000 52100 52200 52300 52400 52500 52600 52700 52800 52900 53000 53100 53200 53300 53400 53500 53600 53700 53800 53900 54000 54100 54200 54300 54400 54500 54600 54700 54800 54900 55000 55100 55200 55300 55400 55500 55600 55700 55800 55900 56000 56100 56200 56300 56400 56500 56600 56700 56800 56900 57000 57100 57200 57300 57400 57500 57600 57700 57800 57900 58000 58100 58200 58300 58400 58500 58600 58700 58800 58900 59000 59100 59200 59300 59400 59500 59600 59700 59800 59900 60000 60100 60200 60300 60400 60500 60600 60700 60800 60900 61000 61100 61200 61300 61400 61500 61600 61700 61800 61900 62000 62100 62200 62300 62400 62500 62600 62700 62800 62900 63000 63100 63200 63300 63400 63500 63600 63700 63800 63900 64000 64100 64200 64300 64400 64500 64600 64700 64800 64900 65000 65100 65200 65300 65400 65500 65600 65700 65800 65900 66000 66100 66200 66300 66400 66500 66600 66700 66800 66900 67000 67100 67200 67300 67400 67500 67600 67700 67800 67900 68000 68100 68200 68300 68400 68500 68600 68700 68800 68900 69000 69100 69200 69300 69400 69500 69600 69700 69800 69900 70000 70100 70200 70300 70400 70500 70600 70700 70800 70900 71000 71100 71200 71300 71400 71500 71600 71700 71800 71900 72000 72100 72200 72300 72400 72500 72600 72700 72800 72900 73000 73100 73200 73300 73400 73500 73600 73700 73800 73900 74000 74100 74200 74300 74400 74500 74600 74700 74800 74900 75000 75100 75200 75300 75400 75500 75600 75700 75800 75900 76000 76100 76200 76300 76400 76500 76600 76700 76800 76900 77000 77100 77200 77300 77400 77500 77600 77700 77800 77900 78000 78100 78200 78300 78400 78500 78600 78700 78800 78900 79000 79100 79200 79300 79400 79500 79600 79700 79800 79900 80000 80100 80200 80300 80400 80500 80600 80700 80800 80900 81000 81100 81200 81300 81400 81500 81600 81700 81800 81900 82000 82100 82200 82300 82400 82500 82600 82700 82800 82900 83000 83100 83200 83300 83400 83500 83600 83700 83800 83900 84000 84100 84200 84300 84400 84500 84600 84700 84800 84900 85000 85100 85200 85300 85400 85500 85600 85700 85800 85900 86000 86100 86200 86300 86400 86500 86600 86700 86800 86900 87000 87100 87200 87300 87400 87500 87600 87700 87800 87900 88000 88100 88200 88300 88400 88500 88600 88700 88800 88900 89000 89100 89200 89300 89400 89500 89600 89700 89800 89900 90000 90100 90200 90300 90400 90500 90600 90700 90800 90900 91000 91100 91200 91300 91400 91500 91600 91700 91800 91900 92000 92100 92200 92300 92400 92500 92600 92700 92800 92900 93000 93100 93200 93300 93400 93500 93600 93700 93800 93900 94000 94100 94200 94300 94400 94500 94600 94700 94800 94900 95000 95100 95200 95300 95400 95500 95600 95700 95800 95900 96000 96100 96200 96300 96400 96500 96600 96700 96800 96900 97000 97100 97200 97300 97400 97500 97600 97700 97800 97900 98000 98100 98200 98300 98400 98500 98600 98700 98800 98900 99000 99100 99200 99300 99400 99500 99600 99700 99800 99900 100000 100100 100200 100300 100400 100500 100600 100700 100800 100900 101000 101100 101200 101300 101400 101500 101600 101700 101800 101900 102000 102100 102200 102300 102400 102500 102600 102700 102800 102900 103000 103100 103200 103300 103400 103500 103600 103700 103800 103900 104000 104100 104200 104300 104400 104500 104600 104700 104800 104900 105000 105100 105200 105300 105400 105500 105600 105700 105800 105900 106000 106100 106200 106300 106400 106500 106600 106700 106800 106900 107000 107100 107200 107300 107400 107500 107600 107700 107800 107900 108000 108100 108200 108300 108400 108500 108600 108700 108800 108900 109000 109100 109200 109300 109400 109500 109600 109700 109800 109900 110000 110100 110200 110300 110400 110500 110600 110700 110800 110900 111000 111100 111200 111300 111400 111500 111600 111700 111800 111900 112000 112100 112200 112300 112400 112500 112600 112700 112800 112900 113000 113100 113200 113300 113400 113500 113600 113700 113800 113900 114000 114100 114200 114300 114400 114500 114600 114700 114800 114900 115000 115100 115200 115300 115400 115500 115600 115700 115800 115900 116000 116100 116200 116300 116400 116500 116600 116700 116800 116900 117000 117100 117200 117300 117400 117500 117600 117700 117800 117900 118000 118100 118200 118300 118400 118500 118600 118700 118800 118900 119000 119100 119200 119300 119400 119500 119600 119700 119800 119900 120000 120100 120200 120300 120400 120500 120600 120700 120800 120900 121000 121100 121200 121300 121400 121500 121600 121700 121800 121900 122000 122100 122200 122300 122400 122500 122600 122700 122800 122900 123000 123100 123200 123300 123400 123500 123600 123700 123800 123900 124000 124100 124200 124300 124400 124500 124600 124700 124800 124900 125000 125100 125200 125300 125400 125500 125600 125700 125800 125900 126000 126100 126200 126300 126400 126500 126600 126700 126800 126900 127000 127100 127200 127300 127400 127500 127600 127700 127800 127900 128000 128100 128200 128300 128400 128500 128600 128700 128800 128900 129000 129100 129200 129300 129400 129500 129600 129700 129800 129900 130000 130100 130200 130300 130400 130500 130600 130700 130800 130900 131000 131100 131200 131300 131400 131500 131600 131700 131800 131900 132000 132100 132200 132300 132400 132500 132600 132700 132800 132900 133000 133100 133200 133300 133400 133500 133600 133700 133800 133900 134000 134100 134200 134300 134400 134500 134600 134700 134800 134900 135000 135100 135200 135300 135400 135500 135600 135700 135800 135900 136000 136100 136200 136300 136400 136500 136600 136700 136800 136900 137000 137100 137200 137300 137400 137500 137600 137700 137800 137900 138000 138100 138200 138300 138400 138500 138600 138700 138800 138900 139000 139100 139200 139300 139400 139500 139600 139700 139800 139900 140000 140100 140200 140300 140400 140500 140600 140700 140800 140900 141000 141100 141200 141300 141400 141500 141600 141700 141800 141900 142000 142100 142200 142300 142400 142500 142600 142700 142800 142900 143000 143100 143200 143300 143400 143500 143600 143700 143800 143900 144000 144100 144200 144300 144400 144500 144600 144700 144800 144900 145000 145100 145200 145300 145400 145500 145600 145700 145800 145900 146000 146100 146200 146300 146400 146500 146600 146700 146800 146900 147000 147100 147200 147300 147400 147500 147600 147700 147800 147900 148000 148100 148200 148300 148400 148500 148600 148700 148800 148900 149000 149100 149200 149300 149400 149500 149600 149700 149800 149900 150000 150100 150200 150300 150400 150500 150600 150700 150800 150900 151000 151100 151200 151300 151400 151500 151600 151700 151800 151900 152000 152100 152200 152300 152400 152500 152600 152700 152800 152900 153000 153100 153200 153300 153400 153500 153600 153700 153800 153900 154000 154100 154200 154300 154400 154500 154600 154700 154800 154900 155000 155100 155200 155300 155400 155500 155600 155700 155800 155900 156000 156100 156200 156300 156400 156500 156600 156700 156800 156900 157000 157100 157200 157300 157400 157500 157600 157700 157800 157900 158000 158100 158200 158300 158400 158500 158600 158700 158800 158900



Appendix B Geotechnical Laboratory Test Results

Geotechnical Investigation for Pre-Construction Support of Future Development

Active Petro-Canada Retail Fuel Outlet No. 65044 6250 Hazeldean Rd, Ottawa, Ontario

Suncor Energy Products Partnership

SLR Project No.: 216.030133.00001

March 11, 2026

February 13, 2026

Mr. Iqbal Budwal
SLR Consulting (Canada) Ltd.
871 Equestrian Ct, 1, Oakville,
ON, L6L 6L7

Project : 26-1060-01

Subject: PNJ Lab 21480 to 21484 Sieve and Hydrometer & Moisture content Testing.

Dear Iqbal:

PNJ has tested the submitted Borehole Split Spoon (SS) samples for various tests requested under submission for Suncor – Hazeldean, Ottawa, Job No. 216.030133.00001.

The samples were delivered to PNJ laboratory on January 27, 2026. A total of five (5) Boreholes samples were received, to be tested for Sieve and Hydrometer & Moisture content. The test reports for each individual test are attached to this letter.

PNJ has tested the samples as per the MTO LS procedures for respective testing. We trust we have conducted this testing within our terms of reference. Should you have any questions, please contact our office.

Yours Truly,



Prabhdeep Lubana, P.Eng.,
Principal
Manager Laboratory Services
PNJ Engineering Inc.

Moisture Content

Client: SLR Consulting

Project No.: 26-1060-01 / 216.030133.00001

Location: Hazeldean, Ottawa


Borehole ID: BH25-09

Lab No.: 21484

Item No.	Sample No.	Depth		Container No.	Weight			Moisture Content (%)
		From	To		Wet (Soil+Tare)	Dry (Soil+Tare)	Tare	
1	SS1	-	-	-	78.6	73.8	46.4	17.5
2	SS3	-	-	-	72.3	54.9	30.5	71.3
3	SS4	-	-	-	57.8	56.6	20.1	3.3
4	SS5	-	-	-	62.8	61.9	20.6	2.2
5	SS6	-	-	-	301.7	286.4	58.4	6.7
6	SS7	-	-	-	67.8	66.2	19.9	3.5
7	SO2	-	-	-	90.1	85.0	20.4	7.9
8	SO3	-	-	-	88.6	83.7	19.9	7.7
9	SO4	-	-	-	79.8	75.9	20.0	7.0
10	SO5	-	-	-	82.2	77.5	20.0	8.2
11	SO7	-	-	-	82.8	78.0	19.9	8.3

Particle Size Analysis of Soils

MTO LS-700, 702, 703/704, 705




% Fines		% Sand			% Gravel	
Clay	Silt	Fine	Medium	Coarse	Fine	Coarse
3.3	4.2	79.1	13.4	0.0	0.0	0.0

Client: SLR Consulting	Lab No.: 21480-6	D10: 0.10779	D30: 0.22299	D60: 0.3353	LL: n/a
Project: Suncor-Hazeldean 216.030133.00001	Project No.: 26-1060-01	D20: 0.16539	D50: 0.3016		PL: n/a
Location: Hazeldean, Ottawa	Borehole: BH25-02	Classification: n/a	In-situ Moisture: 4.1%		PI: n/a
Date: February 12, 2026	Sample: SS6	Sample Description: SAND, trace silt, trace clay			

Particle Size Analysis of Soils

MTO LS-700, 702, 703/704, 705




% Fines		% Sand			% Gravel	
Clay	Silt	Fine	Medium	Coarse	Fine	Coarse
4.1	8.4	34.8	40.4	3.0	9.3	0.0

Client: SLR Consulting	Lab No.: 21481-6	D10: 0.05863	D30: 0.2982	D60: 0.5870	LL: n/a
Project: Suncor-Hazeldean 216.030133.00001	Project No.: 26-1060-01	D20: 0.19715	D50: 0.4593		PL: n/a
Location: Hazeldean, Ottawa	Borehole: BH25-03	Classification: n/a	In-situ Moisture: 3.5%		PI: n/a
Date: February 12, 2026	Sample: SS6	Sample Description: SAND, trace gravel, trace silt, trace clay			

Particle Size Analysis of Soils

MTO LS-700, 702, 703/704, 705




% Fines		% Sand			% Gravel	
Clay	Silt	Fine	Medium	Coarse	Fine	Coarse
4.2	10.7	17.6	26.0	9.3	17.5	14.7

Client: SLR Consulting	Lab No.: 21482-4	D10: 0.03761	D30: 0.3789	D60: 2.4304	LL: n/a
Project: Suncor-Hazeldean 216.030133.00001	Project No.: 26-1060-01	D20: 0.18583	D50: 0.8188		PL: n/a
Location: Hazeldean, Ottawa	Borehole: BH25-06	Classification: n/a	In-situ Moisture: 2.9%		PI: n/a
Date: February 12, 2026	Sample: SS4	Sample Description:	GRAVELLY SAND, some silt, trace clay		

Particle Size Analysis of Soils

MTO LS-700, 702, 703/704, 705




% Fines		% Sand			% Gravel	
Clay	Silt	Fine	Medium	Coarse	Fine	Coarse
2.9	13.5	80.4	2.2	0.4	0.6	0.0

Client: SLR Consulting	Lab No.: 21483-9	D10: 0.05816	D30: 0.10035	D60: 0.1702	LL: n/a
Project: Suncor-Hazeldean 216.030133.00001	Project No.: 26-1060-01	D20: 0.08167	D50: 0.1464		PL: n/a
Location: Hazeldean, Ottawa	Borehole: BH25-08	Classification: n/a	In-situ Moisture: 23.0%		PI: n/a
Date: February 12, 2026	Sample: SS9	Sample Description: SAND, some silt, trace clay, trace gravel			

Particle Size Analysis of Soils

MTO LS-700, 702, 703/704, 705



% Fines		% Sand			% Gravel	
Clay	Silt	Fine	Medium	Coarse	Fine	Coarse
2.0	9.6	66.8	6.1	2.8	1.1	11.6

Client: SLR Consulting	Lab No.: 21484-6	D10: 0.06989	D30: 0.14127	D60: 0.2334	LL: n/a
Project: Suncor-Hazeldean 216.030133.00001	Project No.: 26-1060-01	D20: 0.11056	D50: 0.2027		PL: n/a
Location: Hazeldean, Ottawa	Borehole: BH25-09	Classification: n/a	In-situ Moisture: 6.7%		PI: n/a
Date: February 12, 2026	Sample: SS6	Sample Description: SAND, some gravel, trace silt, trace clay			



Appendix C Certificate of Analysis

Geotechnical Investigation for Pre-Construction Support of Future Development

Active Petro-Canada Retail Fuel Outlet No. 65044 6250 Hazeldean Rd, Ottawa, Ontario

Suncor Energy Products Partnership

SLR Project No.: 216.030133.00001

March 11, 2026

CERTIFICATE OF ANALYSIS

Work Order	: WT2601817	Laboratory	: ALS Environmental - Waterloo
Client	: SLR Consulting (Canada) Ltd.	Account Manager	: Andrew Martin
Contact	: Iqbal Budwal	Address	: 60 Northland Road, Unit 1
Address	: 871 Equestrian Ct Unit 1 Oakville Ontario Canada L6L 6L7	E-mail	: andrew.martin@alsglobal.com
Telephone	: 519-573-7161	Telephone	: +1 519 886 6910
Project	: 216.030136.00001/216.030133.00001	Date Samples Received	: 28-Jan-2026 09:00
PO	: ----	Date Analysis Commenced	: 29-Jan-2026
C-O-C number	: 20-1050639	Issue Date	: 04-Feb-2026 18:45
Sampler	: ----		
Site	: ----		
Quote number	: Ontario - Palmer/SLR 2025/2026 SOA		
No. of samples received	: 4		
No. of samples analysed	: 4		

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QC Interpretive report to assist with Quality Review and Sample Receipt Notification (SRN).

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is conducted in accordance with US FDA 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Laboratory Department</i>
Amanda Ganouri-Lumsden	Department Manager - Microbiology and Prep	Centralized Prep, Waterloo, Ontario
Jon Fisher	Laboratory Manager - Environmental	Inorganics, Waterloo, Ontario
Josphin Masihi	Supervisor I	Centralized Prep, Waterloo, Ontario
Nik Perkio	Senior Analyst	Inorganics, Waterloo, Ontario
Walt Kippenhuck	Supervisor - Inorganic	Inorganics, Waterloo, Ontario



General Comments

The analytical methods used by ALS are developed using internationally recognized reference methods (where available), such as those published by US EPA, APHA Standard Methods, ASTM, ISO, Environment Canada, BC MOE, and Ontario MOE. Refer to the ALS Quality Control Interpretive report (QCI) for applicable references and methodology summaries. Reference methods may incorporate modifications to improve performance.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Please refer to Quality Control Interpretive report (QCI) for information regarding Holding Time compliance.

Key: CAS Number: Chemical Abstracts Services number is a unique identifier assigned to discrete substances.
LOR: Limit of Reporting (detection limit).

<i>Unit</i>	<i>Description</i>
%	percent
mg/kg	milligrams per kilogram
mV	millivolts
ohm cm	ohm centimetres (resistivity)
pH units	pH units
µS/cm	microsiemens per centimetre

<: less than.

>: greater than.

Surrogate: An analyte that is similar in behavior to target analyte(s), but that does not occur naturally in environmental samples. For applicable tests, surrogates are added to samples prior to analysis as a check on recovery.

Test results reported relate only to the samples as received by the laboratory.

UNLESS OTHERWISE STATED on SRN or QCI Report, ALL SAMPLES WERE RECEIVED IN ACCEPTABLE CONDITION.



Analytical Results

Sub-Matrix: Soil (Matrix: Soil/Solid)					Client sample ID	BH26-3 SS-3 ----	BH26-4 SS-4 ----	BH26-8 SS-4 ----	BH26-9 S05 ----	----
Client sampling date / time					27-Jan-2026 16:00	27-Jan-2026 16:00	27-Jan-2026 16:00	27-Jan-2026 16:00	----	----
Analyte	CAS Number	Method/Lab	LOR	Unit	WT2601817-001	WT2601817-002	WT2601817-003	WT2601817-004	----	----
					Result	Result	Result	Result	----	----
Physical Tests										
Conductivity (1:2 leachate)	----	E100-L/WT	5.00	µS/cm	378	1080	297	94.8	----	----
Moisture	----	E144/WT	0.25	%	25.2	28.0	4.72	7.77	----	----
Oxidation-reduction potential [ORP]	----	E125/WT	0.10	mV	387	388	333	356	----	----
pH (1:2 soil:CaCl2-aq)	----	E108A/WT	0.10	pH units	7.69	7.68	8.16	8.05	----	----
Resistivity	----	EC100R/WT	100	ohm cm	2650	930	3370	10500	----	----
Inorganics										
Sulfides, acid volatile	----	E396-L/WT	0.20	mg/kg	<0.26	<0.28	0.26	<0.22	----	----
Leachable Anions & Nutrients										
Chloride, soluble ion content	16887-00-6	E236.Cl/WT	5.0	mg/kg	123	442	107	<5.0	----	----
Sulfate, soluble ion content	14808-79-8	E236.SO4/WT	20	mg/kg	58	85	28	<20	----	----

Please refer to the General Comments section for an explanation of any qualifiers detected.



QUALITY CONTROL INTERPRETIVE REPORT

<p>Work Order : WT2601817</p> <p>Client : SLR Consulting (Canada) Ltd.</p> <p>Contact : Iqbal Budwal</p> <p>Address : 871 Equestrian Ct Unit 1 Oakville ON Canada L6L 6L7</p> <p>Telephone : 519-573-7161</p> <p>Project : 216.030136.00001/216.030133.00001</p> <p>PO : ----</p> <p>C-O-C number : 20-1050639</p> <p>Sampler : ----</p> <p>Site : ----</p> <p>Quote number : Ontario - Palmer/SLR 2025/2026 SOA</p> <p>No. of samples received : 4</p> <p>No. of samples analysed : 4</p>	<p>Page : 1 of 9</p> <p>Laboratory : ALS Environmental - Waterloo</p> <p>Account Manager : Andrew Martin</p> <p>Address : 60 Northland Road, Unit 1 Waterloo, Ontario Canada N2V 2B8</p> <p>Telephone : +1 519 886 6910</p> <p>Date Samples Received : 28-Jan-2026 09:00</p> <p>Issue Date : 04-Feb-2026 18:45</p>
---	---

This report is automatically generated by the ALS LIMS (Laboratory Information Management System) through evaluation of Quality Control (QC) results and other QA parameters associated with this submission, and is intended to facilitate rapid data validation by auditors or reviewers. The report highlights any exceptions and outliers to ALS Data Quality Objectives, provides holding time details and exceptions, summarizes QC sample frequencies, and lists applicable methodology references and summaries.

Key

- Anonymous: Refers to samples which are not part of this work order, but which formed part of the QC process lot.
- CAS Number: Chemical Abstracts Service number is a unique identifier assigned to discrete substances.
- DQO: Data Quality Objective.
- LOR: Limit of Reporting (detection limit).
- RPD: Relative Percent Difference.

Workorder Comments

Holding times are displayed as "----" if no guidance exists from CCME, Canadian provinces, or broadly recognized international references.

Summary of Outliers

Outliers : Quality Control Samples

- No Method Blank value outliers occur.
- No Duplicate outliers occur.
- No Laboratory Control Sample (LCS) outliers occur
- No Test sample Surrogate recovery outliers exist.

Outliers: Reference Material (RM) Samples

- No Reference Material (RM) Sample outliers occur.

Outliers : Analysis Holding Time Compliance (Breaches)

- Analysis Holding Time Outliers exist - please see following pages for full details.

Outliers : Frequency of Quality Control Samples

- No Quality Control Sample Frequency Outliers occur.



Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times, which are selected to meet known provincial and /or federal requirements. In the absence of regulatory hold times, ALS establishes recommendations based on guidelines published by organizations such as CCME, US EPA, APHA Standard Methods, ASTM, or Environment Canada (where available). Dates and holding times reported below represent the first dates of extraction or analysis. If subsequent tests or dilutions exceeded holding times, qualifiers are added (refer to COA).

If samples are identified below as having been analyzed or extracted outside of recommended holding times, measurement uncertainties may be increased, and this should be taken into consideration when interpreting results.

Where actual sampling date is not provided on the chain of custody, the date of receipt with time at 00:00 is used for calculation purposes.

Where only the sample date without time is provided on the chain of custody, the sampling date at 00:00 is used for calculation purposes.

Matrix: Soil/Solid

Evaluation: * = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method Container / Client Sample ID(s)	Method	Sampling Date	Extraction / Preparation				Analysis				
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval	
				Rec	Actual			Rec	Actual		
Inorganics : Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)											
LDPE bag BH26-3 SS-3	E396-L	27-Jan-2026	04-Feb-2026	0 hrs	190 hrs	*	04-Feb-2026	0 hrs	190 hrs	*	UCP
Inorganics : Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)											
LDPE bag BH26-4 SS-4	E396-L	27-Jan-2026	04-Feb-2026	0 hrs	190 hrs	*	04-Feb-2026	0 hrs	190 hrs	*	UCP
Inorganics : Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)											
LDPE bag BH26-8 SS-4	E396-L	27-Jan-2026	04-Feb-2026	0 hrs	190 hrs	*	04-Feb-2026	0 hrs	190 hrs	*	UCP
Inorganics : Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)											
LDPE bag BH26-9 S05	E396-L	27-Jan-2026	04-Feb-2026	0 hrs	190 hrs	*	04-Feb-2026	0 hrs	190 hrs	*	UCP
Leachable Anions & Nutrients : Water Extractable Chloride by IC											
LDPE bag BH26-3 SS-3	E236.Cl	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓	
Leachable Anions & Nutrients : Water Extractable Chloride by IC											
LDPE bag BH26-4 SS-4	E236.Cl	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓	
Leachable Anions & Nutrients : Water Extractable Chloride by IC											
LDPE bag BH26-8 SS-4	E236.Cl	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓	



Matrix: Soil/Solid

Evaluation: * = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method Container / Client Sample ID(s)	Method	Sampling Date	Extraction / Preparation				Analysis			
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval
				Rec	Actual			Rec	Actual	
Leachable Anions & Nutrients : Water Extractable Chloride by IC										
LDPE bag BH26-9 S05	E236.Cl	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓
Leachable Anions & Nutrients : Water Extractable Sulfate by IC										
LDPE bag BH26-3 SS-3	E236.SO4	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓
Leachable Anions & Nutrients : Water Extractable Sulfate by IC										
LDPE bag BH26-4 SS-4	E236.SO4	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓
Leachable Anions & Nutrients : Water Extractable Sulfate by IC										
LDPE bag BH26-8 SS-4	E236.SO4	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓
Leachable Anions & Nutrients : Water Extractable Sulfate by IC										
LDPE bag BH26-9 S05	E236.SO4	27-Jan-2026	03-Feb-2026	30 days	7 days	✓	03-Feb-2026	28 days	0 days	✓
Physical Tests : Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)										
LDPE bag BH26-3 SS-3	E100-L	27-Jan-2026	02-Feb-2026	30 days	6 days	✓	03-Feb-2026	30 days	6 days	✓
Physical Tests : Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)										
LDPE bag BH26-4 SS-4	E100-L	27-Jan-2026	02-Feb-2026	30 days	6 days	✓	03-Feb-2026	30 days	6 days	✓
Physical Tests : Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)										
LDPE bag BH26-8 SS-4	E100-L	27-Jan-2026	02-Feb-2026	30 days	6 days	✓	03-Feb-2026	30 days	6 days	✓
Physical Tests : Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)										
LDPE bag BH26-9 S05	E100-L	27-Jan-2026	02-Feb-2026	30 days	6 days	✓	03-Feb-2026	30 days	6 days	✓



Matrix: Soil/Solid

Evaluation: ✖ = Holding time exceedance ; ✔ = Within Holding Time

Analyte Group : Analytical Method Container / Client Sample ID(s)	Method	Sampling Date	Extraction / Preparation				Analysis				
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval	
				Rec	Actual			Rec	Actual		
Physical Tests : Moisture Content by Gravimetry											
LDPE bag BH26-3 SS-3	E144	27-Jan-2026	----	----	----		29-Jan-2026	----	----		
Physical Tests : Moisture Content by Gravimetry											
LDPE bag BH26-4 SS-4	E144	27-Jan-2026	----	----	----		29-Jan-2026	----	----		
Physical Tests : Moisture Content by Gravimetry											
LDPE bag BH26-8 SS-4	E144	27-Jan-2026	----	----	----		29-Jan-2026	----	----		
Physical Tests : Moisture Content by Gravimetry											
LDPE bag BH26-9 S05	E144	27-Jan-2026	----	----	----		02-Feb-2026	----	----		
Physical Tests : ORP by Electrode											
LDPE bag BH26-3 SS-3	E125	27-Jan-2026	02-Feb-2026	180 days	6 days	✔	04-Feb-2026	180 days	6 days	✔	
Physical Tests : ORP by Electrode											
LDPE bag BH26-4 SS-4	E125	27-Jan-2026	02-Feb-2026	180 days	6 days	✔	04-Feb-2026	180 days	6 days	✔	
Physical Tests : ORP by Electrode											
LDPE bag BH26-8 SS-4	E125	27-Jan-2026	02-Feb-2026	180 days	6 days	✔	04-Feb-2026	180 days	6 days	✔	
Physical Tests : ORP by Electrode											
LDPE bag BH26-9 S05	E125	27-Jan-2026	03-Feb-2026	180 days	7 days	✔	03-Feb-2026	180 days	7 days	✔	
Physical Tests : pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received											
LDPE bag BH26-3 SS-3	E108A	27-Jan-2026	02-Feb-2026	30 days	6 days	✔	02-Feb-2026	30 days	6 days	✔	



Matrix: Soil/Solid

Evaluation: ✖ = Holding time exceedance ; ✔ = Within Holding Time

Analyte Group : Analytical Method Container / Client Sample ID(s)	Method	Sampling Date	Extraction / Preparation				Analysis			
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval
				Rec	Actual			Rec	Actual	
Physical Tests : pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received										
LDPE bag BH26-4 SS-4	E108A	27-Jan-2026	02-Feb-2026	30 days	6 days	✔	02-Feb-2026	30 days	6 days	✔
Physical Tests : pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received										
LDPE bag BH26-8 SS-4	E108A	27-Jan-2026	02-Feb-2026	30 days	6 days	✔	02-Feb-2026	30 days	6 days	✔
Physical Tests : pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received										
LDPE bag BH26-9 S05	E108A	27-Jan-2026	02-Feb-2026	30 days	6 days	✔	02-Feb-2026	30 days	6 days	✔

Legend & Qualifier Definitions

Rec. HT: ALS recommended hold time (see units).



Quality Control Parameter Frequency Compliance

The following report summarizes the frequency of laboratory QC samples analyzed within the analytical batches (QC lots) in which the submitted samples were processed. The actual frequency should be greater than or equal to the expected frequency.

Matrix: **Soil/Solid**

Evaluation: ✖ = QC frequency outside specification; ✔ = QC frequency within specification.

Quality Control Sample Type	Method	QC Lot #	Count		Frequency (%)		
			QC	Regular	Actual	Expected	Evaluation
Analytical Methods							
Laboratory Duplicates (DUP)							
Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)	E100-L	2437669	1	19	5.2	5.0	✔
pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received	E108A	2437730	1	14	7.1	5.0	✔
ORP by Electrode	E125	2438696	2	26	7.6	5.0	✔
Moisture Content by Gravimetry	E144	2433944	2	40	5.0	5.0	✔
Water Extractable Chloride by IC	E236.Cl	2438786	1	13	7.6	5.0	✔
Water Extractable Sulfate by IC	E236.SO4	2438787	1	13	7.6	5.0	✔
Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)	E396-L	2440926	1	13	7.6	4.7	✔
Laboratory Control Samples (LCS)							
Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)	E100-L	2437669	2	19	10.5	10.0	✔
pH by Meter (1:2 Soil:0.01M CaCl2 Extraction) - As Received	E108A	2437730	1	14	7.1	5.0	✔
ORP by Electrode	E125	2438696	2	26	7.6	5.0	✔
Moisture Content by Gravimetry	E144	2433944	2	40	5.0	5.0	✔
Water Extractable Chloride by IC	E236.Cl	2438786	2	13	15.3	10.0	✔
Water Extractable Sulfate by IC	E236.SO4	2438787	2	13	15.3	10.0	✔
Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)	E396-L	2440926	1	13	7.6	4.7	✔
Method Blanks (MB)							
Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)	E100-L	2437669	1	19	5.2	5.0	✔
Moisture Content by Gravimetry	E144	2433944	2	40	5.0	5.0	✔
Water Extractable Chloride by IC	E236.Cl	2438786	1	13	7.6	5.0	✔
Water Extractable Sulfate by IC	E236.SO4	2438787	1	13	7.6	5.0	✔
Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)	E396-L	2440926	1	13	7.6	4.7	✔



Methodology References and Summaries

The analytical methods used by ALS are developed using internationally recognized reference methods (where available), such as those published by US EPA, APHA Standard Methods, ASTM, ISO, Environment Canada, BC MOE, and Ontario MOE. Reference methods may incorporate modifications to improve performance (indicated by "mod").

Analytical Methods	Method / Lab	Matrix	Method Reference	Method Descriptions
Conductivity in Soil (1:2 Soil:Water Extraction) (Low Level)	E100-L ALS Environmental - Waterloo	Soil/Solid	CSSS Ch. 15 (mod)/APHA 2510 (mod)	Conductivity, also known as Electrical Conductivity (EC) or Specific Conductance, is measured by immersion of a conductivity cell with platinum electrodes into a soil sample that has been added in a defined ratio of soil to deionized water, then shaken well and allowed to settle. Conductance is measured in the fluid that is observed in the upper layer.
pH by Meter (1:2 Soil:0.01M CaCl ₂ Extraction) - As Received	E108A ALS Environmental - Waterloo	Soil/Solid	MECP E3530	pH is determined by potentiometric measurement with a pH electrode, and is conducted at ambient laboratory temperature (normally 20 ± 5°C) and is carried out in accordance with procedures described in the Analytical Protocol (prescriptive method). A minimum 10g portion of the sample, as received, is extracted with 20mL of 0.01M calcium chloride solution by shaking for at least 30 minutes. The aqueous layer is separated from the soil by centrifuging, settling, or decanting and then analyzed using a pH meter and electrode. This method is equivalent to ASTM D4972 and is acceptable for topsoil analysis.
ORP by Electrode	E125 ALS Environmental - Waterloo	Soil/Solid	APHA 2580 (mod)	Oxidation Reduction Potential (ORP) is reported as the oxidation-reduction potential of the platinum metal-reference electrode employed in the analysis, measured in mV.
Moisture Content by Gravimetry	E144 ALS Environmental - Waterloo	Soil/Solid	CCME PHC in Soil - Tier 1	Moisture is measured gravimetrically by drying the sample at 105°C. Moisture content is calculated as the weight loss (due to water) divided by the wet weight of the sample, expressed as a percentage.
Water Extractable Chloride by IC	E236.Cl ALS Environmental - Waterloo	Soil/Solid	EPA 300.1	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection using a soil sample that has been added in a defined ratio of soil to deionized water, then shaken well and allowed to settle. Anions are measured in the fluid that is observed in the upper layer.
Water Extractable Sulfate by IC	E236.SO ₄ ALS Environmental - Waterloo	Soil/Solid	EPA 300.1	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection using a soil sample that has been added in a defined ratio of soil to deionized water, then shaken well and allowed to settle. Anions are measured in the fluid that is observed in the upper layer.
Acid Volatile Sulfide in Soil by Colourimetry (0.2 mg/kg)	E396-L ALS Environmental - Waterloo	Soil/Solid	APHA 4500S2J	This analysis is carried out in accordance with the method described in APHA 4500 S2-J. After extraction the Acid Volatile Sulphide is determined colourimetrically.
Resistivity Calculation for Soil Using E100-L	EC100R ALS Environmental - Waterloo	Soil/Solid	APHA 2510 B	Soil Resistivity (calculated) is determined as the inverse of the conductivity of a 2:1 water:soil leachate (dry weight). This method is intended as a rapid approximation for Soil Resistivity. Where high accuracy results are required, direct measurement of Soil Resistivity by the Wenner Four-Electrode Method (ASTM G57) is recommended.
Preparation Methods	Method / Lab	Matrix	Method Reference	Method Descriptions



<i>Preparation Methods</i>	<i>Method / Lab</i>	<i>Matrix</i>	<i>Method Reference</i>	<i>Method Descriptions</i>
Leach 1:2 Soil:Water for pH/EC	EP108 ALS Environmental - Waterloo	Soil/Solid	BC WLAP METHOD: PH, ELECTROMETRIC, SOIL	The procedure involves mixing the dried (at <60°C) and sieved (No. 10 / 2mm) sample with deionized/distilled water at a 1:2 ratio of sediment to water.
Leach 1:2 Soil : 0.01CaCl ₂ - As Received for pH	EP108A ALS Environmental - Waterloo	Soil/Solid	MOEE E3137A	A minimum 10g portion of the sample, as received, is extracted with 20mL of 0.01M calcium chloride solution by shaking for at least 30 minutes. The aqueous layer is separated from the soil by centrifuging, settling or decanting and then analyzed using a pH meter and electrode.
Preparation of ORP by Electrode	EP125 ALS Environmental - Waterloo	Soil/Solid	APHA 2580 (mod)	Field-moist sample is extracted in a 1:2 ratio with DI water and then analyzed by ORP meter.
Anions Leach 1:10 Soil:Water (Dry)	EP236 ALS Environmental - Waterloo	Soil/Solid	EPA 300.1	5 grams of dried soil is mixed with 50 grams of distilled water for a minimum of 30 minutes. The extract is filtered and analyzed by ion chromatography.
Distillation for Acid Volatile Sulfide in Soil	EP396-L ALS Environmental - Waterloo	Soil/Solid	APHA 4500S2J	Acid Volatile Sulfide is determined by colourimetric measurement on a sediment sample that has been treated with hydrochloric acid within a purge and trap system, where the evolved hydrogen sulfide gas is carried into a basic solution by argon gas for analysis.

QUALITY CONTROL REPORT

Work Order : WT2601817

Client : SLR Consulting (Canada) Ltd.
 Contact : Iqbal Budwal
 Address : 871 Equestrian Ct Unit 1
 Oakville ON Canada L6L 6L7
 Telephone : 519-573-7161
 Project : 216.030136.00001/216.030133.00001
 PO : ----
 C-O-C number : 20-1050639
 Sampler : ----
 Site : ----
 Quote number : Ontario - Palmer/SLR 2025/2026 SOA
 No. of samples received : 4
 No. of samples analysed : 4

Laboratory : ALS Environmental - Waterloo
 Account Manager : Andrew Martin
 Address : 60 Northland Road, Unit 1
 Waterloo ON Canada N2V 2B8
 Telephone : +1 519 886 6910
 Date Samples Received : 28-Jan-2026 09:00
 Date Analysis Commenced : 29-Jan-2026
 Issue Date : 04-Feb-2026 18:45

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percent Difference (RPD) and Data Quality Objectives
- @ReferenceMaterial!
- Method Blank (MB) Report; Recovery and Data Quality Objectives
- Laboratory Control Sample (LCS) Report; Recovery and Data Quality Objectives

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is conducted in accordance with US FDA 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Laboratory Department</i>
Amanda Ganouri-Lumsden	Department Manager - Microbiology and Prep	Waterloo Centralized Prep, Waterloo, Ontario
Jon Fisher	Laboratory Manager - Environmental	Waterloo Inorganics, Waterloo, Ontario
Josphin Masihi	Supervisor I	Waterloo Centralized Prep, Waterloo, Ontario
Nik Perkio	Senior Analyst	Waterloo Inorganics, Waterloo, Ontario
Walt Kippenhuck	Supervisor - Inorganic	Waterloo Inorganics, Waterloo, Ontario



General Comments

The ALS Quality Control (QC) report is optionally provided to ALS clients upon request. ALS test methods include comprehensive QC checks with every analysis to ensure our high standards of quality are met. Each QC result has a known or expected target value, which is compared against predetermined Data Quality Objectives (DQOs) to provide confidence in the accuracy of associated test results. This report contains detailed results for all QC results applicable to this sample submission. Please refer to the ALS Quality Control Interpretation report (QCI) for applicable method references and methodology summaries.

Key:

- Anonymous=Refers to samples which are not part of this work order, but which formed part of the QC process lot.
- CAS Number=Chemical Abstracts Service number is a unique identifier assigned to discrete substances.
- DQO=Data Quality Objective.
- LOR=Limit of Reporting (detection limit).
- RPD=Relative Percent Difference
- # =Indicates a QC result that did not meet the ALS DQO.

Workorder Comments

Holding times are displayed as "---" if no guidance exists from CCME, Canadian provinces, or broadly recognized international references.



Laboratory Duplicate (DUP) Report

A Laboratory Duplicate (DUP) is a randomly selected intralaboratory replicate sample. Laboratory Duplicates provide information regarding method precision and sample heterogeneity. ALS DQOs for Laboratory Duplicates are expressed as test-specific limits for Relative Percent Difference (RPD), or as an absolute difference limit of 2 times the LOR for low concentration duplicates within ~ 4-10 times the LOR (cut-off is test specific).

Sub-Matrix: Soil

Laboratory Duplicate (DUP) Report

Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	LOR	Unit	Original Result	Duplicate Result	RPD(%) or Difference	Duplicate Limits	Qualifier
Physical Tests(QC Lot: 2433944)											
WT2601801-001	Anonymous	Moisture	----	E144	0.25	%	12.9	12.5	2.69 %	20%	---
Physical Tests(QC Lot: 2437669)											
WT2601914-001	Anonymous	Conductivity (1:2 leachate)	----	E100-L	5.00	µS/cm	0.131 mS/cm	155	16.6 %	20%	---
Physical Tests(QC Lot: 2437730)											
WT2601919-001	Anonymous	pH (1:2 soil:CaCl2-aq)	----	E108A	0.10	pH units	8.22	8.15	0.855 %	5%	---
Physical Tests(QC Lot: 2437842)											
HA2600307-007	Anonymous	Moisture	----	E144	0.25	%	9.64	9.84	2.07 %	20%	---
Physical Tests(QC Lot: 2438654)											
WT2601801-001	Anonymous	Oxidation-reduction potential [ORP]	----	E125	0.10	mV	332	326	1.82 %	25%	---
Physical Tests(QC Lot: 2438696)											
WT2601742-003	Anonymous	Oxidation-reduction potential [ORP]	----	E125	0.10	mV	372	375	0.803 %	25%	---
Inorganics(QC Lot: 2440926)											
TY2600665-001	Anonymous	Sulfides, acid volatile	----	E396-L	0.24	mg/kg	<0.24	<0.24	0	Diff <2x LOR	---
Leachable Anions & Nutrients(QC Lot: 2438786)											
WT2601808-004	Anonymous	Chloride, soluble ion content	16887-00-6	E236.Cl	5.0	mg/kg	42.0	41.0	2.34 %	30%	---
Leachable Anions & Nutrients(QC Lot: 2438787)											
WT2601808-004	Anonymous	Sulfate, soluble ion content	14808-79-8	E236.SO4	20	mg/kg	362	354	2.22 %	30%	---



Method Blank (MB) Report

A Method Blank is an analyte-free matrix that undergoes sample processing identical to that carried out for test samples. Method Blank results are used to monitor and control for potential contamination from the laboratory environment and reagents. For most tests, the DQO for Method Blanks is for the result to be < LOR.

Sub-Matrix: Soil/Solid

Analyte	CAS Number	Method	LOR	Unit	Result	Qualifier
Physical Tests(QC Lot: 2433944)						
Moisture	----	E144	0.25	%	<0.25	----
Physical Tests(QC Lot: 2437669)						
Conductivity (1:2 leachate)	----	E100-L	5	µS/cm	<5.00	----
Physical Tests(QC Lot: 2437730)						
pH (1:2 soil:CaCl2-aq)	----	E108A	----	pH units	----	----
Physical Tests(QC Lot: 2437842)						
Moisture	----	E144	0.25	%	<0.25	----
Inorganics(QC Lot: 2440926)						
Sulfides, acid volatile	----	E396-L	0.2	mg/kg	<0.20	----
Leachable Anions & Nutrients(QC Lot: 2438786)						
Chloride, soluble ion content	16887-00-6	E236.Cl	5	mg/kg	<5.0	----
Leachable Anions & Nutrients(QC Lot: 2438787)						
Sulfate, soluble ion content	14808-79-8	E236.SO4	20	mg/kg	<20	----



Laboratory Control Sample (LCS) Report

A Laboratory Control Sample (LCS) is an analyte-free matrix that has been fortified (spiked) with test analytes at known concentration and processed in an identical manner to test samples. LCS results are expressed as percent recovery, and are used to monitor and control test method accuracy and precision, independent of test sample matrix.

Sub-Matrix: Soil

					Laboratory Control Sample (LCS) Report				
					Spike	Recovery (%)	Recovery Limits (%)		
Analyte	CAS Number	Method	LOR	Unit	Target Concentration	LCS	Low	High	Qualifier
Physical Tests(QC Lot: 2433944)									
Moisture	----	E144	0.25	%	50 %	99.5	90.0	110	----
Physical Tests(QC Lot: 2437669)									
Conductivity (1:2 leachate)	----	E100-L	5	µS/cm	1409 µS/cm	98.0	90.0	110	----
Physical Tests(QC Lot: 2437730)									
pH (1:2 soil:CaCl2-aq)	----	E108A	----	pH units	7 pH units	101	98.0	102	----
Physical Tests(QC Lot: 2437842)									
Moisture	----	E144	0.25	%	50 %	99.5	90.0	110	----
Inorganics(QC Lot: 2440926)									
Sulfides, acid volatile	----	E396-L	0.2	mg/kg	100 mg/kg	85.0	70.0	130	----
Leachable Anions & Nutrients(QC Lot: 2438786)									
Chloride, soluble ion content	16887-00-6	E236.Cl	5	mg/kg	1000 mg/kg	99.2	80.0	120	----
Leachable Anions & Nutrients(QC Lot: 2438787)									
Sulfate, soluble ion content	14808-79-8	E236.SO4	20	mg/kg	1000 mg/kg	100.0	80.0	120	----



Reference Material (RM) Report

A Reference Material (RM) is a homogenous material with known and well-established analyte concentrations. RMs are processed in an identical manner to test samples, and are used to monitor and control the accuracy and precision of a test method for a typical sample matrix. RM results are expressed as percent recovery of the target analyte concentration. RM targets may be certified target concentrations provided by the RM supplier, or may be ALS long-term mean values (for empirical test methods).



Sub-Matrix: Soil

Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	Reference Material (RM) Report					
					Target Concentration	Original Result	Recovery (%)	Recovery Limits (%)		Qualifier
						LCS	Low	High		
Physical Tests(QC Lot: 2437669)										
QC-MRG2-2437669001		Conductivity (1:2 leachate)	----	E100-L	714.1 µS/cm	714.1 µS/cm		70.0	130	----
Physical Tests(QC Lot: 2438654)										
QC-MRG2-2438653001		Oxidation-reduction potential [ORP]	----	E125	475 mV	475 mV		90.0	110	----
Physical Tests(QC Lot: 2438696)										
QC-MRG2-2438695001		Oxidation-reduction potential [ORP]	----	E125	475 mV	475 mV		90.0	110	----
Leachable Anions & Nutrients(QC Lot: 2438786)										
QC-MRG2-2438786001		Chloride, soluble ion content	16887-00-6	E236.Cl	495 mg/kg	495 mg/kg		70.0	130	----
Leachable Anions & Nutrients(QC Lot: 2438787)										
QC-MRG2-2438786001		Sulfate, soluble ion content	14808-79-8	E236.SO4	493 mg/kg	493 mg/kg		70.0	130	----



SM SOL-542
www.alsglobal.com

Chain of Custody (COC) / Analytical Request Form

Canada Toll Free: 1 800 668 9878

COC Number: 20-1050639

Page
Environmental Division
Waterloo
Work Order Reference
WT2601817

Contact and company name below will appear on the final report

Report To: SLR Consulting Ltd.
 Company: Lebel Building
 Contact: 437-560-4866
 Phone: Company address below will appear on the final report
 Street: 871 Gageshiana Ct
 City/Province: Parisville
 Postal Code: V4R 6L7
 Invoice To: Same as Report To YES NO
 Copy of Invoice with Report: YES NO

Select Report Format: PDF EXCEL BDD (XLS/TXL)
 Merge QC/QCI Reports with COA: YES NO N/A
 Compare Results to Criteria on Report - provide details below if box checked
 Select Distribution: EMAIL MAIL FAX
 Email 1 or Fax: lebel.building@scrsociety.ca
 Email 2:
 Email 3:
 Invoice Recipients: EMAIL MAIL FAX
 Select Invoice Distribution: EMAIL MAIL FAX
 Email 1 or Fax: lebel.building@scrsociety.ca
 Email 2:
 Email 3:

Turnaround Time (TAT) Requested
 Routine [R] if received by 3pm M-F - no surcharges apply
 4 day [P4] if received by 3pm M-F - 20% rush surcharge minimum
 3 day [P3] if received by 3pm M-F - 25% rush surcharge minimum
 2 day [P2] if received by 3pm M-F - 50% rush surcharge minimum
 1 day [E] if received by 3pm M-F - 100% rush surcharge minimum
 Same day [E2] if received by 10am M-S - 200% rush surcharge. Address may apply to rush requests on weekends, statutory holidays and non-rail
 Date and Time Required for all ESP TATs:
 For all tests with rush TATs requested, please see Analysis Requir

ALS Account # / Quote #: 216.030136, 00001/216.030133
 Job #: 216.030133
 PO / AFE:
 LSD:

ALS Lab Work Order #: WT2601817 MD
 Sample Identification and/or Coordinates (This description will appear on the report)
 BH 26-3 SS-3
 BH 26-4 SS-4
 BH 25-8 SS-4
 BH 25-9 SS-4

ALS Sample # (ALS use only)	Date (dd-mm-yy)	Time (hh:mm)	Sample Type
	27-Jan-26	4:00	Soil
	27-Jan-26	4:00	Soil
	27-Jan-26	4:00	Soil
	27-Jan-26	4:00	Soil

ALS Sample # (ALS use only)	Date (dd-mm-yy)	Time (hh:mm)	Sample Type

Shipping Water (DW) Samples (client use)
 YES NO
 Are samples taken from a Regulated DW System?
 YES NO
 Are samples for human consumption/ use?
 YES NO

Notes / Specify Limits for result evaluation by selecting from drop-down below (Excel COC only)

ALS Sample # (ALS use only)	Date (dd-mm-yy)	Time (hh:mm)	Sample Type	NUMBER OF CONTAINERS
	27-Jan-26	4:00	Soil	1
	27-Jan-26	4:00	Soil	1
	27-Jan-26	4:00	Soil	1
	27-Jan-26	4:00	Soil	1

Released by: DL Date: 27-Jan-26 Time: 5:30
 SHIPMENT RELEASE (client use)

Received by: FM Date: 28-Jan-26 Time: 9:00
 INITIAL SHIPMENT RECEPTION (ALS use only)

Received by: AP Date: 28-Jan-26 Time: 1:30
 FINAL SHIPMENT RECEPTION (ALS use only)


REFER TO BACK PAGE FOR ALS LOCATIONS AND SAMPLING INFORMATION
 Failure to complete all portions of this form may delay analysis. Please fill in this form LEGIBLY. By the use of this form the user acknowledges and agrees with the Terms and Conditions as specified on the back page of the white - report copy.
 1. If any water samples are taken from a Regulated Drinking Water (DW) System, please submit using an Authorized DW COC form.

WHITE - LABORATORY COPY
 YELLOW - CLIENT COPY

SAMPLE RECEIPT DETAILS (ALS use only)
 Cooling Method: NONE ICE ICE PACKS FROZEN COOLING INITIATED
 Submission Comments Identified on Sample Receipt Notification: YES N/A NO
 Cooler Custody Seals Intact: YES N/A NO
 INITIAL COOLER TEMPERATURES °C: 5.2
 FINAL COOLER TEMPERATURES °C: 4.8



Telephone: +1 519 886 6910



Making Sustainability Happen