ALL BARRIER-FREE PARKING SPACES SHALL BE PROVIDED WITH:
1. VERTICAL SIGNAGE:
   a) MIN. 300mm WIDE x 600mm HIGH
   b) MOUNTED AT A HEIGHT OF 1.5m - 2.0m FROM THE GROUND
   c) OF CONTRASTING COLOUR, WITH THE BACKGROUND ENVIRONMENT
2. PAVEMENT MARKING THAT ARE:
   a) MIN. 1525mm x 1525mm
   b) SLIP RESISTANT
   c) CLEARLY VISIBLE THROUGH THE USE OF HIGH TONAL CONTRAST TO THE SURFACE OF THE PARKING SPACE
   d) LOCATED NEAR THE BACK OF THE SPACE



2 / A012 BF PARKING PLAN
1 : 100

BICYCLE PARKING DETAIL


HOLES ARE PRESENT ONLY WHEN GALVANIZED OPTION IS SPECIFIED
STEEL ANCHOR TAB IS WELDED TO THE BOTTOM OF THE POST TO HELP FIXATE THE ASSEMBLY IN THE CONCRETE FOOTING
FORMED FROM 50mm O.D. SCHEDULE 40 STEEL PIPE
RECOMMENDED HEIGHT
CONCRETE FOOTING
SOIL CONDITIONS
AVAILABLE OPTIONS:
POWDER COATED
GALVANIZED (AFTER FABRICATION)
CUSTOM COLORS (INCLUDING THE ALL PANSY AT AN ADDITIONAL COST)
ALL POWDER COATED FINISHES ARE SHINY AT FACTORY STANDARD. INC. (TO MATCH THE VIS PRODUCT LINE)
OTHER FINISHES ON APPROVED OPTIONS (WHITE PRESSED)
MOUNTING
SURFACE MOUNTED (AS SHOWN) OR FLUSH MOUNTED IN GROUND (AS SHOWN) AND SURFACE
NOTES:
1. DRAWINGS NOT TO SCALE, DO NOT SCALE DRAWINGS.
2. ALL FABRICATED METAL ITEMS SHALL BE STEEL, UNLESS NOTED OTHERWISE. BOLTS, HARDWARES, FITTINGS, AND ELECTRODES SHALL BE COMPATIBLE WITH BASE METAL AND SHALL NOT STAIN STEEL. ALL STEEL SURFACES SHALL BE SHOP CLEANED AND PREPARED TO RECEIVE SHOP PRIMER AND FINISH COATS AS SPECIFIED. ALL WELDS SHALL BE CONTINUOUS, CONFORMING TO CSA STANDARD W59-M1989 (LATEST REVISION) AND SHALL BE PERFORMED BY WELDERS CERTIFIED TO CSA STANDARD W47.1-M1983 (LATEST REVISION). ALL WELDS SHALL BE GROUND SMOOTH AND FREE OF SPATTER. ALL EXPOSED WELDS SHALL BE CONTINUOUS